LORC_EL1, LORegion Control (EL1)

The LORC_EL1 characteristics are:

Purpose

Enables and disables LORegions, and selects the current LORegion descriptor.

Configuration

This register is present only when FEAT_LOR is implemented. Otherwise, direct accesses to LORC_EL1 are undefined.

If no LORegion descriptors are supported by the PE, then this register is res0.

Attributes

LORC_EL1 is a 64-bit register.

Field descriptions



Bits [63:10]

Reserved, res0.

DS, bits [9:2]

Descriptor Select. Selects the current LORegion descriptor accessed by LORSA_EL1, LOREA_EL1, and LORN_EL1.

The number of LORegion descriptors in implementation defined. The maximum number of LORegion descriptors supported is 256. If the number is less than 256, then bits[63:M+2] are res0, where M is Log_2(Number of LORegion descriptors supported by the implementation).

If this field points to an LORegion descriptor that is not supported by an implementation, then the registers LORN_EL1, LOREA_EL1, and LORSA_EL1 are res0.

The reset behavior of this field is:

- On a Warm reset, this field resets to an architecturally unknown value.

Bit [1]

Reserved, res0.

EN, bit [0]

Enable. Indicates whether LORegions are enabled.

EN	Meaning
0b0	Disabled. Memory accesses do not match any LORegions.
0b1	Enabled. Memory accesses may match a LORegion.

This bit is permitted to be cached in a TLB.

The reset behavior of this field is:

- On a Warm reset, this field resets to 0.

Accessing LORC_EL1

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, LORC_EL1

op0	op1	CRn	CRm	op2
0b11	0b000	0b1010	0b0100	0b011

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.TLOR == '1' then
        UNDEFINED;
    elsif SCR_EL3.NS == '0' then
        UNDEFINED;
    elsif EL2Enabled() && HCR_EL2.TLOR == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
SCR_EL3.FGTEn == '1') && HFGRTR_EL2.LORC_EL1 == '1'
```

```
then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && SCR_EL3.TLOR == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = LORC_EL1;
elsif PSTATE.EL == EL2 then
    if SCR_EL3.NS == '0' then
        UNDEFINED;
    elsif Halted() && HaveEL(EL3) && EDSCR.SDD ==
'1' && boolean IMPLEMENTATION_DEFINED "EL3 trap
priority when SDD == '1'" && SCR_EL3.TLOR == '1' then
        UNDEFINED;
    elsif HaveEL(EL3) && SCR_EL3.TLOR == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = LORC_EL1;
elsif PSTATE.EL == EL3 then
    if SCR_EL3.NS == '0' then
        UNDEFINED;
    else
        X[t, 64] = LORC_EL1;
```

MSR LORC_EL1, <Xt>

op0	op1	CRn	CRm	op2
0b11	0b000	0b1010	0b0100	0b011

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.TLOR == '1' then
        UNDEFINED;
    elsif SCR_EL3.NS == '0' then
        UNDEFINED;
    elsif EL2Enabled() && HCR_EL2.TLOR == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
SCR_EL3.FGTEn == '1') && HFGWTR_EL2.LORC_EL1 == '1'
then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && SCR_EL3.TLOR == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
```

```
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
        else
            LORC_EL1 = X[t, 64];
    elsif PSTATE.EL == EL2 then
        if SCR_EL3.NS == '0' then
            UNDEFINED;
        elsif Halted() && HaveEL(EL3) && EDSCR.SDD ==
    '1' && boolean IMPLEMENTATION_DEFINED "EL3 trap
    priority when SDD == '1'" && SCR_EL3.TLOR == '1' then
            UNDEFINED;
        elsif HaveEL(EL3) && SCR_EL3.TLOR == '1' then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
        else
            LORC_EL1 = X[t, 64];
    elsif PSTATE.EL == EL3 then
        if SCR_EL3.NS == '0' then
            UNDEFINED;
        else
            LORC_EL1 = X[t, 64];
```

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94