



**SQRDMLSH** <Vd>.<T>, <Vn>.<T>, <Vm>.<Ts>[<index>]

```
if !IsFeatureImplemented(FEAT_RDM) then UNDEFINED;

constant integer idxdsize = 64 << UInt(H);
integer index;
bit Rmhi;
case size of
    when '01' index = UInt(H:L:M); Rmhi = '0';
    when '10' index = UInt(H:L); Rmhi = M;
    otherwise UNDEFINED;

integer d = UInt(Rd);
integer n = UInt(Rn);
integer m = UInt(Rmhi:Rm);

constant integer esize = 8 << UInt(size);
constant integer datasize = 64 << UInt(Q);
integer elements = datasize DIV esize;

boolean rounding = TRUE;
boolean sub_op = (S == '1');
```

## Assembler Symbols

<V>

Is a width specifier, encoded in “size”:

size	<V>
00	RESERVED
01	H
10	S
11	RESERVED

<d>

Is the number of the SIMD&FP destination register, encoded in the "Rd" field.

<n>

Is the number of the first SIMD&FP source register, encoded in the "Rn" field.

<Vd>

Is the name of the SIMD&FP destination register, encoded in the "Rd" field.

<T>

Is an arrangement specifier, encoded in “size:Q”:

size	Q	<T>
00	x	RESERVED
01	0	4H
01	1	8H
10	0	2S
10	1	4S
11	x	RESERVED

<Vn> Is the name of the first SIMD&FP source register, encoded in the "Rn" field.

<Vm> Is the name of the second SIMD&FP source register, encoded in "size:M:Rm":

size	<Vm>
00	RESERVED
01	0:Rm
10	M:Rm
11	RESERVED

Restricted to V0-V15 when element size <Ts> is H.

<Ts> Is an element size specifier, encoded in "size":

size	<Ts>
00	RESERVED
01	H
10	S
11	RESERVED

<index> Is the element index, encoded in "size:L:H:M":

size	<index>
00	RESERVED
01	H:L:M
10	H:L
11	RESERVED

## Operation

```
CheckFPAdvSIMDEnabled64();
bits(datasize) operand1 = V[n, datasize];
bits(idxsizesize) operand2 = V[m, idxdsizesize];
bits(datasize) operand3 = V[d, datasize];
bits(datasize) result;
integer element1;
integer element2;
integer element3;
integer accum;
boolean sat;

element2 = SInt(Elem[operand2, index, esize]);
for e = 0 to elements-1
    element1 = SInt(Elem[operand1, e, esize]);
    element3 = SInt(Elem[operand3, e, esize]);
    if sub_op then
        accum = (element3 << esize) - 2 * (element1 * element2);
    else
        accum = (element3 << esize) + 2 * (element1 * element2);
```

```
accum = RShr(accum, esize, rounding);  
(Elem[result, e, esize], sat) = SignedSatQ(accum, esize);  
if sat then FPSR.QC = '1';
```

```
V[d, datasize] = result;
```

---

[Base  
Instructions](#)

[SIMD&FP  
Instructions](#)

[SVE  
Instructions](#)

[SME  
Instructions](#)

[Index by  
Encoding](#)

[Sh  
Pseu](#)

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode  
no\_diffs\_2023\_09\_RC2, sve v2023-06\_rel ; Build timestamp: 2023-09-18T17:56

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This  
document is Non-Confidential.