DBGAUTHSTATUS_EL1, Debug Authentication Status Register

The DBGAUTHSTATUS_EL1 characteristics are:

Purpose

Provides information about the state of the implementation defined authentication interface for debug.

Configuration

AArch64 System register DBGAUTHSTATUS_EL1 bits [31:0] are architecturally mapped to AArch32 System register DBGAUTHSTATUS[31:0].

AArch64 System register DBGAUTHSTATUS_EL1 bits [31:0] are architecturally mapped to External register DBGAUTHSTATUS_EL1[31:0].

Attributes

DBGAUTHSTATUS_EL1 is a 64-bit register.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
RES0																														
RES0					RTNID		RTID		RES0								RLNID		RLID		RES0				SNID		SID		NSNID		NSID	
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0

Bits [63:28]

Reserved, res0.

RTNID, bits [27:26]

Root non-invasive debug.

This field has the same value as DBGAUTHSTATUS_EL1.RTID.

RTID, bits [25:24]

Root invasive debug.

RTID	Meaning

0b00	Not implemented.
0b10	Implemented and disabled. `ExternalRootInvasiveDebugEnabled()` == FALSE.
0b11	Implemented and enabled. `ExternalRootInvasiveDebugEnabled()` == TRUE.

All other values are reserved.

If FEAT_RME is not implemented, the only permitted value is `0b00`.

Bits [23:16]

Reserved, res0.

RLNID, bits [15:14]

Realm non-invasive debug.

This field has the same value as DBGAUTHSTATUS_EL1.RLID.

RLID, bits [13:12]

Realm invasive debug.

RLID	Meaning
0b00	Not implemented.
0b10	Implemented and disabled. `ExternalRealmInvasiveDebugEnabled()` == FALSE.
0b11	Implemented and enabled. `ExternalRealmInvasiveDebugEnabled()` == TRUE.

All other values are reserved.

If FEAT_RME is not implemented, the only permitted value is `0b00`.

Bits [11:8]

Reserved, res0.

SNID, bits [7:6]
When FEAT_Debugv8p4 is implemented:

Secure non-invasive debug.

This field has the same value as DBGAUTHSTATUS_EL1.SID.

Otherwise:

Secure non-invasive debug.

SNID	Meaning
0b00	Not implemented. One of the following is true: • EL3 is not implemented and the Effective value of [SCR_EL3](#).NS is 1. • FEAT_RME is implemented without Secure state.
0b10	Implemented and disabled. ExternalSecureNoninvasiveDebugEnabled() == FALSE.
0b11	Implemented and enabled. ExternalSecureNoninvasiveDebugEnabled() == TRUE.

All other values are reserved.

SID, bits [5:4]

Secure invasive debug.

SID	Meaning
0b00	Not implemented. One of the following is true: • EL3 is not implemented and the Effective value of [SCR_EL3](#).NS is 1. • FEAT_RME is implemented without Secure state.
0b10	Implemented and disabled. ExternalSecureInvasiveDebugEnabled() == FALSE.
0b11	Implemented and enabled. ExternalSecureInvasiveDebugEnabled() == TRUE.

All other values are reserved.

NSNID, bits [3:2]
When FEAT_Debugv8p4 is implemented:

Non-secure non-invasive debug.

NSNID	Meaning

	0b00	Not implemented. EL3 is not implemented and the Effective value of SCR_EL3.NS is 0.
	0b11	Implemented and enabled. EL3 is implemented or the Effective value of SCR_EL3.NS is 1.

All other values are reserved.

Otherwise:

Non-secure non-invasive debug.

NSNID	Meaning
0b00	Not implemented. EL3 is not implemented and the Effective value of SCR_EL3.NS is 0.
0b10	Implemented and disabled. ExternalNoninvasiveDebugEnabled() == FALSE.
0b11	Implemented and enabled. ExternalNoninvasiveDebugEnabled() == TRUE.

All other values are reserved.

NSID, bits [1:0]

Non-secure invasive debug.

NSID	Meaning
0b00	Not implemented. EL3 is not implemented and the Effective value of SCR_EL3.NS is 0.
0b10	Implemented and disabled. ExternalInvasiveDebugEnabled() == FALSE.
0b11	Implemented and enabled. ExternalInvasiveDebugEnabled() == TRUE.

All other values are reserved.

Accessing DBGAUTHSTATUS_EL1

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, DBGAUTHSTATUS_EL1

op0	op1	CRn	CRm	op2
0b10	0b000	0b0111	0b1110	0b110

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && MDCR_EL3.TDA == '1' then
        UNDEFINED;
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
SCR_EL3.FGTEn == '1') &&
HDFGRTR_EL2.DBGAUTHSTATUS_EL1 == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() && MDCR_EL2.<TDE,TDA> != '00'
then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && MDCR_EL3.TDA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = DBGAUTHSTATUS_EL1;
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && MDCR_EL3.TDA == '1' then
        UNDEFINED;
    elsif HaveEL(EL3) && MDCR_EL3.TDA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = DBGAUTHSTATUS_EL1;
elsif PSTATE.EL == EL3 then
    X[t, 64] = DBGAUTHSTATUS_EL1;
```