

MPAMVPM1_EL2, MPAM Virtual PARTID Mapping Register 1

The MPAMVPM1_EL2 characteristics are:

Purpose

MPAMVPM1_EL2 provides mappings from virtual PARTIDs 4 - 7 to physical PARTIDs.

[MPAMIDR_EL1](#).VPMR_MAX field gives the index of the highest implemented [MPAMVPM0_EL2](#) to [MPAMVPM7_EL2](#) registers. VPMR_MAX can be as large as 7 (8 registers) or 32 virtual PARTIDs. If [MPAMIDR_EL1](#).VPMR_MAX == 0, there is only a single MPAMVPM<n>_EL2 register, [MPAMVPM0_EL2](#).

Virtual PARTID mapping is enabled by [MPAMHCR_EL2](#).EL1_VPMEN for PARTIDs in [MPAM1_EL1](#) and by MPAMHCR_EL2.EL0_VPMEN for PARTIDs in [MPAM0_EL1](#).

A virtual-to-physical PARTID mapping entry, PhyPARTID<n>, is valid only when the [MPAMVPMV_EL2](#).VPM_V bit in bit position n is set to 1.

Configuration

This register is present only when FEAT_MPAM is implemented, MPAMIDR_EL1.HAS_HCR == 1 and UInt(MPAMIDR_EL1.VPMR_MAX) > 0. Otherwise, direct accesses to MPAMVPM1_EL2 are undefined.

This register has no effect if EL2 is not enabled in the current Security state.

Attributes

MPAMVPM1_EL2 is a 64-bit register.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
PhyPARTID7																PhyPARTID6															
PhyPARTID5																PhyPARTID4															
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0

PhyPARTID7, bits [63:48]

Virtual PARTID Mapping Entry for virtual PARTID 7. PhyPARTID7 gives the mapping of virtual PARTID 7 to a physical PARTID.

The reset behavior of this field is:

- On a Warm reset, this field resets to an architecturally unknown value.

PhyPARTID6, bits [47:32]

Virtual PARTID Mapping Entry for virtual PARTID 6. PhyPARTID6 gives the mapping of virtual PARTID 6 to a physical PARTID.

The reset behavior of this field is:

- On a Warm reset, this field resets to an architecturally unknown value.

PhyPARTID5, bits [31:16]

Virtual PARTID Mapping Entry for virtual PARTID 5. PhyPARTID5 gives the mapping of virtual PARTID 5 to a physical PARTID.

The reset behavior of this field is:

- On a Warm reset, this field resets to an architecturally unknown value.

PhyPARTID4, bits [15:0]

Virtual PARTID Mapping Entry for virtual PARTID 4. PhyPARTID4 gives the mapping of virtual PARTID 4 to a physical PARTID.

The reset behavior of this field is:

- On a Warm reset, this field resets to an architecturally unknown value.

Accessing MPAMVPM1_EL2

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, MPAMVPM1_EL2

op0	op1	CRn	CRm	op2
0b11	0b100	0b1010	0b0110	0b001

```

if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.<NV2,NV> == '11' then
        X[t, 64] = NVMem[0x948];
    elsif EL2Enabled() && HCR_EL2.NV == '1' then
        if HaveEL(EL3) && MPAM3_EL3.TRAPLOWER == '1'
then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
            else
                AArch64.SystemAccessTrap(EL2, 0x18);
        else
            UNDEFINED;
    elsif PSTATE.EL == EL2 then
        if HaveEL(EL3) && MPAM3_EL3.TRAPLOWER == '1' then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
        else
            X[t, 64] = MPAMVPM1_EL2;
    elsif PSTATE.EL == EL3 then
        X[t, 64] = MPAMVPM1_EL2;

```

MSR MPAMVPM1_EL2, <Xt>

op0	op1	CRn	CRm	op2
0b11	0b100	0b1010	0b0110	0b001

```

if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.<NV2,NV> == '11' then
        NVMem[0x948] = X[t, 64];
    elsif EL2Enabled() && HCR_EL2.NV == '1' then
        if HaveEL(EL3) && MPAM3_EL3.TRAPLOWER == '1'
then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
            else
                AArch64.SystemAccessTrap(EL2, 0x18);
        else
            UNDEFINED;
    elsif PSTATE.EL == EL2 then
        if HaveEL(EL3) && MPAM3_EL3.TRAPLOWER == '1' then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;

```

```
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            MPAMVPM1_EL2 = X[t, 64];
    elsif PSTATE.EL == EL3 then
        MPAMVPM1_EL2 = X[t, 64];
```

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.