ndex by	Sh
Incoding	Pseud

BaseSIMD&FPSVESMEIndex byInstructionsInstructionsInstructionsInstructionsEncoding

UMULLB (vectors)

Unsigned multiply long (bottom)

Multiply the corresponding even-numbered unsigned elements of the first and second source vectors, and place the results in the overlapping double-width elements of the destination vector. This instruction is unpredicated.

31	30	29	28	27	26	25	24	23 22	21	20 19 18 17 16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	1	0	0	0	1	0	1	size	0	Zm	0	1	1	1	1	0			Zn					Zd		
															$\overline{\Pi}$	T										

```
UMULLB <Zd>.<T>, <Zn>.<Tb>, <Zm>.<Tb>

if !HaveSVE2() && !HaveSME() then UNDEFINED;

if size == '00' then UNDEFINED;

constant integer esize = 8 << UInt(size);

integer n = UInt(Zn);

integer m = UInt(Zm);

integer d = UInt(Zd);</pre>
```

Assembler Symbols

<Zd>

Is the name of the destination scalable vector register, encoded in the "Zd" field.

<T>

Is the size specifier, encoded in "size":

size	<t></t>
0.0	RESERVED
01	Н
10	S
11	D

<Zn>

Is the name of the first source scalable vector register, encoded in the "Zn" field.

<Tb>

Is the size specifier, encoded in "size":

size	<tb></tb>
0.0	RESERVED
01	В
10	Н
11	S

<7m>

Is the name of the second source scalable vector register, encoded in the "Zm" field.

Operation

```
CheckSVEEnabled();
constant integer VL = CurrentVL;
constant integer elements = VL DIV esize;
bits(VL) operand1 = Z[n, VL];
bits(VL) operand2 = Z[m, VL];
bits(VL) result;

for e = 0 to elements-1
   integer element1 = UInt(Elem[operand1, 2*e + 0, esize DIV 2]);
   integer element2 = UInt(Elem[operand2, 2*e + 0, esize DIV 2]);
   integer res = element1 * element2;
   Elem[result, e, esize] = res<esize-1:0>;
Z[d, VL] = result;
```

Operational information

If FEAT_SVE2 is implemented or FEAT_SME is implemented, then if PSTATE.DIT is 1:

- The execution time of this instruction is independent of:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.
- The response of this instruction to asynchronous exceptions does not vary based on:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.

BaseSIMD&FPSVESMEIndex byInstructionsInstructionsInstructionsInstructions

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode no diffs 2023 09 RC2, sve v2023-06 rel ; Build timestamp: 2023-09-18T17:56

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.

Sh Pseu