Index by	Sh
Encoding	Pseud

SIMD&FP **SME** Base **SVE** Ē Instructions **Instructions** Instructions Instructions

SQSUB (immediate)

Signed saturating subtract immediate (unpredicated)

Signed saturating subtract of an unsigned immediate from each element of the source vector, and destructively place the results in the corresponding elements of the source vector. Each result element is saturated to the N-bit element's signed integer range $-2^{(N-1)}$ to $(2^{(N-1)})-1$. This instruction is unpredicated.

The immediate is an unsigned value in the range 0 to 255, and for element widths of 16 bits or higher it may also be a positive multiple of 256 in the range 256 to 65280.

The immediate is encoded in 8 bits with an optional left shift by 8. The preferred disassembly when the shift option is specified is "#<uimm8>, LSL #8". However an assembler and disassembler may also allow use of the shifted 16-bit value unless the immediate is 0 and the shift amount is 8. which must be unambiguously described as "#0, LSL #8".

```
31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5
0 0 1 0 0 1 0 1 size 1 0 0 1 1 0 1 1 sh
                                                      imm8
                                     U
```

```
SQSUB <Zdn>.<T>, <Zdn>.<T>, #<imm>{, <shift>}
```

```
if ! <a href="HaveSVE">HaveSME</a>() then UNDEFINED;
if size:sh == '001' then UNDEFINED;
constant integer esize = 8 << UInt(size);</pre>
integer dn = UInt(Zdn);
integer imm = <u>UInt</u>(imm8);
if sh == '1' then imm = imm << 8;
boolean unsigned = FALSE;
```

Assembler Symbols

<Zdn>

Is the name of the source and destination scalable vector register, encoded in the "Zdn" field.

<T>

Is the size specifier, encoded in "size":

size	<t></t>
00	В
01	Н
10	S
11	D

<imm>

Is an unsigned immediate in the range 0 to 255, encoded in the "imm8" field.

Is the optional left shift to apply to the immediate, defaulting to LSL #0 and encoded in "sh":

sh	<shift></shift>
0	LSL #0
1	LSL #8

Operation

```
CheckSVEEnabled();
constant integer VL = CurrentVL;
constant integer elements = VL DIV esize;
bits(VL) operand1 = Z[dn, VL];
bits(VL) result;

for e = 0 to elements-1
   integer element1 = Int(Elem[operand1, e, esize], unsigned);
   (Elem[result, e, esize], -) = SatQ(element1 - imm, esize, unsigned)
Z[dn, VL] = result;
```

Operational information

This instruction might be immediately preceded in program order by a MOVPRFX instruction. The MOVPRFX instruction must conform to all of the following requirements, otherwise the behavior of the MOVPRFX and this instruction is unpredictable:

- The MOVPRFX instruction must be unpredicated.
- The MOVPRFX instruction must specify the same destination register as this instruction.
- The destination register must not refer to architectural register state referenced by any other source operand register of this instruction.

<u>Base SIMD&FP SVE SME Index by</u> <u>Instructions Instructions Instructions Encoding</u>

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode no_diffs_2023_09_RC2, sve v2023-06_rel; Build timestamp: 2023-09-18T17:56

Copyright \hat{A} © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.

Sh Pseu