

PRFM (immediate)

Prefetch Memory (immediate) signals the memory system that data memory accesses from a specified address are likely to occur in the near future. The memory system can respond by taking actions that are expected to speed up the memory accesses when they do occur, such as preloading the cache line containing the specified address into one or more caches.

The effect of a P_{RFM} instruction is implementation defined. For more information, see *Prefetch memory*.

For information about memory accesses, see *Load/Store addressing modes*.

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	1	1	1	0	0	1	1	0	imm12												Rn				Rt					
size										opc																					

PRFM (<prfop>|<#imm5>), [<Xn|SP>{, #<pimm>}]

bits(64) offset = LSL(ZeroExtend(imm12, 64), 3);

Assembler Symbols

<prfop>	Is the prefetch operation, defined as <type><target><policy>. <type> is one of: PLD Prefetch for load, encoded in the "Rt<4:3>" field as 0b00. PLI Preload instructions, encoded in the "Rt<4:3>" field as 0b01. PST Prefetch for store, encoded in the "Rt<4:3>" field as 0b10. <target> is one of: L1 Level 1 cache, encoded in the "Rt<2:1>" field as 0b00. L2 Level 2 cache, encoded in the "Rt<2:1>" field as 0b01. L3 Level 3 cache, encoded in the "Rt<2:1>" field as 0b10. SLC When FEAT_PRFMSLC is implemented, system level cache, encoded in the "Rt<2:1>" field as 0b11. <policy> is one of: KEEP Retained or temporal prefetch, allocated in the cache normally. Encoded in the "Rt<0>" field as 0. STRM Streaming or non-temporal prefetch, for data that is used only once. Encoded in the "Rt<0>" field as 1. For more information on these prefetch operations, see Prefetch memory . For other encodings of the "Rt" field, use <imm5>.
<imm5>	Is the prefetch operation encoding as an immediate, in the range 0 to 31, encoded in the "Rt" field. This syntax is only for encodings that are not accessible using <prfop>.
<Xn SP>	Is the 64-bit name of the general-purpose base register or stack pointer, encoded in the "Rn" field.

<pimm> Is the optional positive immediate byte offset, a multiple of 8 in the range 0 to 32760, defaulting to 0 and encoded in the "imm12" field as <pimm>/8.

Shared Decode

```
integer n = UInt(Rn);  
integer t = UInt(Rt);
```

Operation

```
bits(64) address;  
  
if n == 31 then  
    address = SP[];  
else  
    address = X[n, 64];  
  
address = address + offset;  
  
Prefetch(address, t<4:0>);
```

[Base
Instructions](#)

[SIMD&FP
Instructions](#)

[SVE
Instructions](#)

[SME
Instructions](#)

[Index by
Encoding](#)

[Sh
Pseud](#)

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode
no_diffs_2023_09_RC2, sve v2023-06_rel ; Build timestamp: 2023-09-18T17:56

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This
document is Non-Confidential.