HFGWTR2_EL2, Hypervisor Fine-Grained Write Trap Register 2

The HFGWTR2_EL2 characteristics are:

Purpose

Provides controls for traps of MSR and MCR writes of System registers.

Configuration

This register is present only when FEAT_FGT2 is implemented. Otherwise, direct accesses to HFGWTR2_EL2 are undefined.

Attributes

HFGWTR2_EL2 is a 64-bit register.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
RES0																															
RES0																													nRCWSMASK_EL1	RES0	nPFAR_EL1

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
RES0																															

Bits [63:3]

Reserved, res0.

nRCWSMASK_EL1, bit [2]

When FEAT_THE is implemented:

Trap MSR or MSRR writes of RCWSMASK_EL1 at EL1 using AArch64 to EL2.

nRCWSMASK_EL1	Meaning

0b0	If EL2 is implemented and enabled in the current Security state, then MSR or MSRR writes of RCWSMASK_EL1 at EL1 using AArch64 are trapped to EL2 and reported with EC syndrome value 0x18 for 64-bit access and 0x14 for 128-bit access, unless the write generates a higher priority exception.
0b1	MSR or MSRR writes of RCWSMASK_EL1 are not trapped by this mechanism.

This field is ignored by the PE and treated as zero when all of the following are true:

- EL3 is implemented.
- SCR_EL3.FGTEn2 == 0.

The reset behavior of this field is:

- On a Warm reset:
  - When EL3 is not implemented, this field resets to 0.
  - Otherwise, this field resets to an architecturally unknown value.

Otherwise:

Reserved, res0.

Bit [1]

Reserved, res0.

nPFAR_EL1, bit [0]
When FEAT_PFAR is implemented:

Trap MSR writes of PFAR_EL1 at EL1 using AArch64 to EL2.

nPFAR_EL1	Meaning
0b0	If EL2 is implemented and enabled in the current Security state, then MSR writes of PFAR_EL1 at EL1 using AArch64 are trapped to EL2 and reported with EC syndrome value 0x18, unless the write generates a higher priority exception.
0b1	MSR writes of PFAR_EL1 are not trapped by this mechanism.

This field is ignored by the PE and treated as zero when all of the following are true:

- EL3 is implemented.
- SCR_EL3.FGTEn2 == 0.

The reset behavior of this field is:

- On a Warm reset:
  - When EL3 is not implemented, this field resets to 0.
  - Otherwise, this field resets to an architecturally unknown value.

Otherwise:

Reserved, res0.

Accessing HFGWTR2_EL2

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, HFGWTR2_EL2

op0	op1	CRn	CRm	op2
0b11	0b100	0b0011	0b0001	0b011

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
```

```
    if EL2Enabled() && HCR_EL2.<NV2,NV> == '11' then
        X[t, 64] = NVMem[0x2C8];
    elsif EL2Enabled() && HCR_EL2.NV == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    else
        UNDEFINED;
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.FGTEn2 == '0' then
        UNDEFINED;
    elsif HaveEL(EL3) && SCR_EL3.FGTEn2 == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = HFGWTR2_EL2;
elsif PSTATE.EL == EL3 then
    X[t, 64] = HFGWTR2_EL2;
```

MSR HFGWTR2_EL2, <Xt>

op0	op1	CRn	CRm	op2
0b11	0b100	0b0011	0b0001	0b011

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.<NV2,NV> == '11' then
        NVMem[0x2C8] = X[t, 64];
    elsif EL2Enabled() && HCR_EL2.NV == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    else
        UNDEFINED;
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.FGTEn2 == '0' then
        UNDEFINED;
    elsif HaveEL(EL3) && SCR_EL3.FGTEn2 == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        HFGWTR2_EL2 = X[t, 64];
elsif PSTATE.EL == EL3 then
    HFGWTR2_EL2 = X[t, 64];
```

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94