GMID_EL1, Multiple tag transfer ID Register

The GMID_EL1 characteristics are:

Purpose

Indicates the block size that is accessed by the LDGM and STGM System instructions.

Configuration

This register is present only when FEAT_MTE2 is implemented. Otherwise, direct accesses to GMID_EL1 are undefined.

Attributes

GMID_EL1 is a 64-bit register.

Field descriptions



Bits [63:4]

Reserved, res0.

BS, bits [3:0]

Log_2 of the block size in words. The minimum supported size is 16B (value == 2) and the maximum is 256B (value == 6).

Accessing GMID_EL1

Accesses to this register use the following encodings in the System register encoding space:

```
MRS <Xt>, GMID_EL1
```

op0	op1	CRn	CRm	op2

0b11	0b001	0b0000	0b0000	0b100

```
if PSTATE.EL == EL0 then
    if IsFeatureImplemented(FEAT_IDST) then
        if EL2Enabled() && HCR_EL2.TGE == '1' then
            AArch64.SystemAccessTrap(EL2, 0x18);
        else
            AArch64.SystemAccessTrap(EL1, 0x18);
    else
        UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.TID5 == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    else
        X[t, 64] = GMID_EL1;
elsif PSTATE.EL == EL2 then
    X[t, 64] = GMID_EL1;
elsif PSTATE.EL == EL3 then
    X[t, 64] = GMID_EL1;
```

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94