<u>c by</u>	<u>Sh</u>
ding	Pseud

LD1SW (vector plus immediate)

Gather load signed words to vector (immediate index)

Gather load of signed words to active elements of a vector register from memory addresses generated by a vector base plus immediate index. The index is a multiple of 4 in the range 0 to 124. Inactive elements will not cause a read from Device memory or signal faults, and are set to zero in the destination vector.

This instruction is illegal when executed in Streaming SVE mode, unless FEAT SME FA64 is implemented and enabled.

```
31302928272625 24 23 22212019181716151413121110 9 8 7 6 5 4 3 2 1 0

1 1 0 0 0 1 0 1 0 0 1 imm5 1 0 0 Pg Zn Zt

msz<1>msz<0> U ff
```

```
LD1SW { <Zt>.D }, <Pq>/Z, [<Zn>.D{, #<imm>}]
```

```
if ! HaveSVE() then UNDEFINED;
integer t = UInt(Zt);
integer n = UInt(Zn);
integer g = UInt(Pg);
constant integer esize = 64;
constant integer msize = 32;
boolean unsigned = FALSE;
integer offset = UInt(imm5);
```

Assembler Symbols

<zt></zt>	Is the name of the scalable vector register to be transferred, encoded in the "Zt" field.
<pg></pg>	Is the name of the governing scalable predicate register P0-P7, encoded in the "Pg" field.
<zn></zn>	Is the name of the base scalable vector register, encoded in the "Zn" field.
<imm></imm>	Is the optional unsigned immediate byte offset, a multiple of 4 in the range 0 to 124, defaulting to 0, encoded in the "imm5" field.

Operation

```
CheckNonStreamingSVEEnabled();
constant integer VL = CurrentVL;
constant integer PL = VL DIV 8;
constant integer elements = VL DIV esize;
bits(PL) mask = P[g, PL];
bits(VL) base;
bits(VL) result;
```

```
bits (msize) data;
constant integer mbytes = msize DIV 8;
boolean contiguous = FALSE;
boolean nontemporal = FALSE;
boolean tagchecked = TRUE;
AccessDescriptor accdesc = CreateAccDescSVE (MemOp_LOAD, nontemporal, co
if <a href="mailto:AnyActiveElement">AnyActiveElement</a> (mask, esize) then
    base = \mathbb{Z}[n, VL];
for e = 0 to elements-1
    if <a href="ActivePredicateElement">ActivePredicateElement</a> (mask, e, esize) then
         bits(64) addr = ZeroExtend(Elem[base, e, esize], 64) + offset *
         data = Mem[addr, mbytes, accdesc];
         Elem[result, e, esize] = Extend(data, esize, unsigned);
    else
         Elem[result, e, esize] = Zeros(esize);
Z[t, VL] = result;
```

Operational information

If FEAT_SVE2 is implemented or FEAT_SME is implemented, then if PSTATE.DIT is 1, the timing of this instruction is insensitive to the value of the data being loaded or stored when its governing predicate register contains the same value for each execution.

 $Internal\ version\ only: is a\ v33.64,\ AdvSIMD\ v29.12,\ pseudocode\ no_diffs_2023_09_RC2,\ sve\ v2023-06_rel\ ;\ Build\ timestamp:\ 2023-09-18T17:56$

Sh

Pseu

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.