

## ST2G

Store Allocation Tags stores an Allocation Tag to two Tag granules of memory. The address used for the store is calculated from the base register and an immediate signed offset scaled by the Tag granule. The Allocation Tag is calculated from the Logical Address Tag in the source register.

This instruction generates an Unchecked access.

It has encodings from 3 classes: [Post-index](#) , [Pre-index](#) and [Signed offset](#)

### Post-index (FEAT\_MTE)

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	1	1	0	0	1	1	0	1										0	1										

**ST2G** [<Xt | SP>](#), [[<Xn | SP>](#)], #[<sim>](#)

```
if !IsFeatureImplemented(FEAT_MTE) then UNDEFINED;
integer n = UInt(Xn);
integer t = UInt(Xt);
bits(64) offset = LSL(SignExtend(imm9, 64), LOG2\_TAG\_GRANULE);
boolean writeback = TRUE;
boolean postindex = TRUE;
```

### Pre-index (FEAT\_MTE)

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	1	1	0	0	1	1	0	1										1	1										

**ST2G** [<Xt | SP>](#), [[<Xn | SP>](#), #[<sim>](#)]

```
if !IsFeatureImplemented(FEAT_MTE) then UNDEFINED;
integer n = UInt(Xn);
integer t = UInt(Xt);
bits(64) offset = LSL(SignExtend(imm9, 64), LOG2\_TAG\_GRANULE);
boolean writeback = TRUE;
boolean postindex = FALSE;
```

### Signed offset (FEAT\_MTE)

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	1	1	0	0	1	1	0	1										1	0										

**ST2G** [<Xt | SP>](#), [[<Xn | SP>](#){, #[<sim>](#)}]

```
if !IsFeatureImplemented(FEAT_MTE) then UNDEFINED;
integer n = UInt(Xn);
integer t = UInt(Xt);
bits(64) offset = LSL(SignExtend(imm9, 64), LOG2\_TAG\_GRANULE);
```

```
boolean writeback = FALSE;
boolean postindex = FALSE;
```

## Assembler Symbols

- <Xt|SP> Is the 64-bit name of the general-purpose source register or stack pointer, encoded in the "Xt" field.
- <Xn|SP> Is the 64-bit name of the general-purpose base register or stack pointer, encoded in the "Xn" field.
- <simm> Is the optional signed immediate offset, a multiple of 16 in the range -4096 to 4080, defaulting to 0 and encoded in the "imm9" field.

## Operation

```
bits(64) address;
bits(64) data = if t == 31 then SP[] else X[t, 64];
bits(4) tag = AArch64.AllocationTagFromAddress(data);

if n == 31 then
    CheckSPAlignment();
    address = SP[];
else
    address = X[n, 64];

if !postindex then
    address = address + offset;

AccessDescriptor accdesc = CreateAccDescLDGSTG(MemOp_STORE);

AArch64.MemTag[address, accdesc] = tag;
AArch64.MemTag[address+TAG\_GRANULE, accdesc] = tag;

if writeback then
    if postindex then
        address = address + offset;

    if n == 31 then
        SP[] = address;
    else
        X[n, 64] = address;
```

---

[Base  
Instructions](#)

[SIMD&FP  
Instructions](#)

[SVE  
Instructions](#)

[SME  
Instructions](#)

[Index by  
Encoding](#)

[Sh  
Pseud](#)

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode  
no\_diffs\_2023\_09\_RC2, sve v2023-06\_rel ; Build timestamp: 2023-09-18T17:56

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This  
document is Non-Confidential.