

USDOT (multiple and indexed vector)

Multi-vector unsigned by signed integer dot-product by indexed element

The unsigned by signed integer dot product instruction computes the dot product of four unsigned 8-bit integer values held in each 32-bit element of the two or four first source vectors and four signed 8-bit integer values in the corresponding indexed 32-bit element of the second source vector. The widened dot product result is destructively added to the corresponding 32-bit element of the ZA single-vector groups.

The groups within the second source vector are specified using an immediate element index which selects the same group position within each 128-bit vector segment. The index range is from 0 to 3, encoded in 2 bits. The vector numbers forming the single-vector group within each half of or each quarter of the ZA array are selected by the sum of the vector select register and immediate offset, modulo half or quarter the number of ZA array vectors.

The vector group symbol, VGx2 or VGx4, indicates that the ZA operand consists of two or four ZA single-vector groups respectively. The vector group symbol is preferred for disassembly, but optional in assembler source code.

This instruction is unpredicated.

It has encodings from 2 classes: [Two ZA single-vectors](#) and [Four ZA single-vectors](#)

Two ZA single-vectors (FEAT_SME2)

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	0	0	0	0	1	0	1	0	1	Zm			0	Rv	1	i2	Zn			1	0	1	off3			U			

USDOT ZA.S[<Wv>, <offs>{, VGx2}], { <Zn1>.B-<Zn2>.B }, <Zm>.B[<index>]

```
if !HaveSME2() then UNDEFINED;
integer v = UInt('010':Rv);
constant integer esize = 32;
integer n = UInt(Zn:'0');
integer m = UInt('0':Zm);
integer offset = UInt(off3);
integer index = UInt(i2);
constant integer nreg = 2;
```

Four ZA single-vectors (FEAT_SME2)

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	0	0	0	0	1	0	1	0	1	Zm			1	Rv	1	i2	Zn			0	1	0	1	off3			U		

```
USDOT ZA.S[<Wv>, <offs>{, VGx4}], { <Zn1>.B-<Zn4>.B }, <Zm>.B[<index>]
```

```
if !HaveSME2() then UNDEFINED;
integer v = UInt('010':Rv);
constant integer esize = 32;
integer n = UInt(Zn:'00');
integer m = UInt('0':Zm);
integer offset = UInt(off3);
integer index = UInt(i2);
constant integer nreg = 4;
```

Assembler Symbols

<Wv>	Is the 32-bit name of the vector select register W8-W11, encoded in the "Rv" field.
<offs>	Is the vector select offset, in the range 0 to 7, encoded in the "off3" field.
<Zn1>	For the two ZA single-vectors variant: is the name of the first scalable vector register of a multi-vector sequence, encoded as "Zn" times 2. For the four ZA single-vectors variant: is the name of the first scalable vector register of a multi-vector sequence, encoded as "Zn" times 4.
<Zn4>	Is the name of the fourth scalable vector register of a multi-vector sequence, encoded as "Zn" times 4 plus 3.
<Zn2>	Is the name of the second scalable vector register of a multi-vector sequence, encoded as "Zn" times 2 plus 1.
<Zm>	Is the name of the second source scalable vector register Z0-Z15, encoded in the "Zm" field.
<index>	Is the immediate index of a 32-bit group of four 8-bit values within each 128-bit vector segment, in the range 0 to 3, encoded in the "i2" field.

Operation

```
CheckStreamingSVEAndZAAEnabled();
constant integer VL = CurrentVL;
constant integer elements = VL DIV esize;
integer vectors = VL DIV 8;
integer vstride = vectors DIV nreg;
integer eltsperssegment = 128 DIV esize;
bits(32) vbase = X[v, 32];
integer vec = (UInt(vbase) + offset) MOD vstride;
bits(VL) result;

for r = 0 to nreg-1
    bits(VL) operand1 = Z[n+r, VL];
    bits(VL) operand2 = Z[m, VL];
    bits(VL) operand3 = ZAvector[vec, VL];
```

```

for e = 0 to elements-1
    bits(esize) sum = Elem[operand3, e, esize];
    integer segmentbase = e - (e MOD eltspersegment);
    integer s = segmentbase + index;
    for i = 0 to 3
        integer element1 = UInt(Elem[operand1, 4 * e + i, esize DIV
        integer element2 = SInt(Elem[operand2, 4 * s + i, esize DIV
        sum = sum + element1 * element2;
    Elem[result, e, esize] = sum;
ZAvector[vec, VL] = result;
vec = vec + vstride;

```

[Base
Instructions](#)

[SIMD&FP
Instructions](#)

[SVE
Instructions](#)

[SME
Instructions](#)

[Index by
Encoding](#)

[Sh
Pseu](#)

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode
no_diffs_2023_09_RC2, sve v2023-06_rel ; Build timestamp: 2023-09-18T17:56

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This
document is Non-Confidential.