<u>c by</u>	<u>Sh</u>
ding	<u>Pseuc</u>

<u>Base</u>	SIMD&FP	<u>SVE</u>	<u>SME</u>	Index by
<u>Instructions</u>	<u>Instructions</u>	<u>Instructions</u>	<u>Instructions</u>	<b>Encoding</b>

## **UMULH** (unpredicated)

Unsigned multiply returning high half (unpredicated)

Widening multiply unsigned integer values of all elements of the first source vector by corresponding elements of the second source vector and place the high half of the result in the corresponding elements of the destination vector. This instruction is unpredicated.

31 30	29	28	27	26	25	24	23 22	21	20 19 18 17 16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0 0	0	0	0	1	0	0	size	1	Zm	0	1	1	0	1	1			Zn					Zd		
															П										

```
UMULH <Zd>.<T>, <Zn>.<T>, <Zm>.<T>

if !HaveSVE2() && !HaveSME() then UNDEFINED;

constant integer esize = 8 << UInt(size);

integer n = UInt(Zn);

integer m = UInt(Zm);

integer d = UInt(Zd);

boolean unsigned = TRUE;</pre>
```

## **Assembler Symbols**

<Zd> Is the name of the destination scalable vector register, encoded in the "Zd" field.

<T>

Is the size specifier, encoded in "size":

size	<t></t>
0.0	В
01	Н
10	S
11	D

<Zn> Is the name of the first source scalable vector register, encoded in the "Zn" field.

<Zm> Is the name of the second source scalable vector register, encoded in the "Zm" field.

## Operation

```
CheckSVEEnabled();
constant integer VL = CurrentVL;
constant integer elements = VL DIV esize;
bits(VL) operand1 = Z[n, VL];
bits(VL) operand2 = Z[m, VL];
bits(VL) result;
```

```
for e = 0 to elements-1
   integer element1 = Int(Elem[operand1, e, esize], unsigned);
   integer element2 = Int(Elem[operand2, e, esize], unsigned);
   integer product = (element1 * element2) >> esize;
   Elem[result, e, esize] = product<esize-1:0>;
Z[d, VL] = result;
```

## **Operational information**

If FEAT\_SVE2 is implemented or FEAT\_SME is implemented, then if PSTATE.DIT is 1:

- The execution time of this instruction is independent of:
  - The values of the data supplied in any of its registers.
  - The values of the NZCV flags.
- The response of this instruction to asynchronous exceptions does not vary based on:
  - The values of the data supplied in any of its registers.
  - The values of the NZCV flags.

BaseSIMD&FPSVESMEIndex byInstructionsInstructionsInstructionsInstructionsEncoding

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode no diffs 2023 09 RC2, sve v2023-06 rel ; Build timestamp: 2023-09-18T17:56

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.

Sh Pseu