

TRCCIDCVR<n>, Context Identifier Comparator Value Registers <n>, n = 0 - 7

The TRCCIDCVR<n> characteristics are:

Purpose

Contains a Context identifier value.

Configuration

AArch64 System register TRCCIDCVR<n> bits [63:0] are architecturally mapped to External register [TRCCIDCVR<n>\[63:0\]](#).

This register is present only when FEAT_ETE is implemented, FEAT_TRC_SR is implemented and $\text{UInt}(\text{TRCIDR4.NUMCIDC}) > n$. Otherwise, direct accesses to TRCCIDCVR<n> are undefined.

Attributes

TRCCIDCVR<n> is a 64-bit register.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
VALUE																															
VALUE																															
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0

VALUE, bits [63:0]

Context identifier value. The width of this field is indicated by [TRCIDR2.CIDSIZE](#). Unimplemented bits are res0. After a PE Reset, the trace unit assumes that the Context identifier is zero until the PE updates the Context identifier.

The reset behavior of this field is:

- On a Trace unit reset, this field resets to an architecturally unknown value.

Accessing TRCCIDCVR<n>

Must be programmed if any of the following are true:

- [TRCRSCTLR<a>](#).GROUP == 0b0110 and [TRCRSCTLR<a>](#).CID[n] == 1.
- [TRCACATR<a>](#).CONTEXTTYPE == 0b01 or 0b11 and [TRCACATR<a>](#).CONTEXT == n.

Writes are constrained unpredictable if the trace unit is not in the Idle state.

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, TRCCIDCVR<m> ; Where m = 0-7

op0	op1	CRn	CRm	op2
0b10	0b001	0b0011	m[2:0]:0b0	0b000

```
integer m = UInt(CRm<3:1>);

if m >= NUM_TRACE_CONTEXT_IDENTIFIER_COMPARATORS then
    UNDEFINED;
elsif PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
    && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
    when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
    elsif CPACR_EL1.TTA == '1' then
        AArch64.SystemAccessTrap(EL1, 0x18);
    elsif EL2Enabled() && CPTR_EL2.TTA == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
    IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
    SCR_EL3.FGTEn == '1') && HDFGRTR_EL2.TRC == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            X[t, 64] = TRCCIDCVR[m];
    elsif PSTATE.EL == EL2 then
        if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
        && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
        when SDD == '1'" && CPTR_EL3.TTA == '1' then
            UNDEFINED;
        elsif CPTR_EL2.TTA == '1' then
```

```

        AArch64.SystemAccessTrap(EL2, 0x18);
    elseif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            X[t, 64] = TRCCIDCVR[m];
    elseif PSTATE.EL == EL3 then
        if CPTR_EL3.TTA == '1' then
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            X[t, 64] = TRCCIDCVR[m];

```

MSR TRCCIDCVR<m>, <Xt> ; Where m = 0-7

op0	op1	CRn	CRm	op2
0b10	0b001	0b0011	m[2:0]:0b0	0b000

```

integer m = UInt(CRm<3:1>);

if m >= NUM_TRACE_CONTEXT_IDENTIFIER_COMPARATORS then
    UNDEFINED;
elseif PSTATE.EL == EL0 then
    UNDEFINED;
elseif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
    && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
    when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
    elseif CPACR_EL1.TTA == '1' then
        AArch64.SystemAccessTrap(EL1, 0x18);
    elseif EL2Enabled() && CPTR_EL2.TTA == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elseif EL2Enabled() &&
    IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
    SCR_EL3.FGTEn == '1') && HDFGWTR_EL2.TRC == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elseif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        TRCCIDCVR[m] = X[t, 64];
    elseif PSTATE.EL == EL2 then
        if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
        && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
        when SDD == '1'" && CPTR_EL3.TTA == '1' then
            UNDEFINED;
        elseif CPTR_EL2.TTA == '1' then
            AArch64.SystemAccessTrap(EL2, 0x18);
        elseif HaveEL(EL3) && CPTR_EL3.TTA == '1' then

```

```

        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            TRCCIDCVR[m] = X[t, 64];
    elsif PSTATE.EL == EL3 then
        if CPTR_EL3.TTA == '1' then
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            TRCCIDCVR[m] = X[t, 64];

```

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.