
TLBI VAE1, TLBI VAE1NXS, TLB Invalidate by VA, EL1

The TLBI VAE1, TLBI VAE1NXS characteristics are:

Purpose

Invalidates cached copies of translation table entries from TLBs that meet all the following requirements:

- The entry is a 64-bit stage 1 translation table entry.
Or, if FEAT_D128 is implemented, and the entry is 128-bit a stage 1 translation table entry, if TTL[3:2] is 0b00.
- The entry would be used to translate the specified VA, and one of the following applies:
 - The entry is from a level of lookup above the final level and matches the specified ASID.
 - The entry is a global entry from the final level of lookup.
 - The entry is a non-global entry from the final level of lookup that matches the specified ASID.
- When EL2 is implemented and enabled in the current Security state:
 - If [HCR_EL2](#).{E2H, TGE} is not {1, 1}, the entry would be used with the current VMID and would be required to translate the specified VA using the EL1&0 translation regime for the Security state.
 - If [HCR_EL2](#).{E2H, TGE} is {1, 1}, the entry would be required to translate the specified VA using the EL2&0 translation regime for the Security state.
- When EL2 is not implemented or is disabled in the current Security state, the entry would be required to translate the specified VA using the EL1&0 translation regime for the Security state.

The Security state is indicated by the value of [SCR_EL3](#).NS if FEAT_RME is not implemented, or [SCR_EL3](#).{NSE, NS} if FEAT_RME is implemented.

The invalidation applies to the PE that executes this System instruction.

If FEAT_XS is implemented, the nXS variant of this System instruction is defined.

Both variants perform the same invalidation, but the TLBI System instruction without the nXS qualifier waits for all memory accesses using in-scope old translation information to complete before it is considered complete.

The TLBI System instruction with the nXS qualifier is considered complete when the subset of these memory accesses with XS attribute set to 0 are complete.

Configuration

There are no configuration notes.

Attributes

TLBI VAE1, TLBI VAE1NXS is a 64-bit System instruction.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32	
ASID																TTL			VA[55:12]													
VA[55:12]																																
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	

ASID, bits [63:48]

ASID value to match. Any TLB entries that match the ASID value and VA value will be affected by this System instruction.

Global TLB entries that match the VA value will be affected by this System instruction, regardless of the value of the ASID field.

If the implementation supports 16 bits of ASID, then the upper 8 bits of the ASID must be written to 0 by software when the context being invalidated only uses 8 bits.

TTL, bits [47:44]

When FEAT_TTL is implemented:

Translation Table Level. Indicates the level of the translation table walk that holds the leaf entry for the address being invalidated.

TTL	Meaning
0b00xx	No information supplied as to the translation table level. Hardware must assume that the entry can be from any level. In this case, TTL<1:0> is res0.

0b01xx	<p>The entry comes from a 4KB translation granule. The level of walk for the leaf level 0bxx is encoded as:</p> <p>0b00 : If FEAT_LPA2 is implemented, level 0. Otherwise, treat as if TTL<3:2> is 0b00.</p> <p>0b01 : Level 1.</p> <p>0b10 : Level 2.</p> <p>0b11 : Level 3.</p>
0b10xx	<p>The entry comes from a 16KB translation granule. The level of walk for the leaf level 0bxx is encoded as:</p> <p>0b00 : Reserved. Treat as if TTL<3:2> is 0b00.</p> <p>0b01 : If FEAT_LPA2 is implemented, level 1. Otherwise, treat as if TTL<3:2> is 0b00.</p> <p>0b10 : Level 2.</p> <p>0b11 : Level 3.</p>
0b11xx	<p>The entry comes from a 64KB translation granule. The level of walk for the leaf level 0bxx is encoded as:</p> <p>0b00 : Reserved. Treat as if TTL<3:2> is 0b00.</p> <p>0b01 : Level 1.</p> <p>0b10 : Level 2.</p> <p>0b11 : Level 3.</p>

If an incorrect value of the TTL field is specified for the entry being invalidated by the instruction, then no entries are required by the architecture to be invalidated from the TLB.

Otherwise:

Reserved, res0.

VA[55:12], bits [43:0]

Bits[55:12] of the virtual address to match. Any appropriate TLB entries that match the ASID value (if appropriate) and VA will be affected by this System instruction.

If the TLB maintenance instructions are targeting a translation regime that is using AArch32, and so has a VA of only 32 bits, then the software must treat bits[55:32] as res0.

The treatment of the low-order bits of this field depends on the translation granule size, as follows:

- Where a 4KB translation granule is being used, all bits are valid and used for the invalidation.
- Where a 16KB translation granule is being used, bits [1:0] of this field are res0 and ignored when the instruction is executed, because VA[13:12] have no effect on the operation of the instruction.
- Where a 64KB translation granule is being used, bits [3:0] of this field are res0 and ignored when the instruction is executed, because VA[15:12] have no effect on the operation of the instruction.

Executing TLBI VAE1, TLBI VAE1NXS

Accesses to this instruction use the following encodings in the System instruction encoding space:

TLBI VAE1{, <Xt>}

op0	op1	CRn	CRm	op2
0b01	0b000	0b1000	0b0111	0b001

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elseif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.TTLB == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elseif EL2Enabled() &&
        IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
        SCR_EL3.FGTEn == '1') && HFGITR_EL2.TLBIVAE1 == '1'
    then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elseif EL2Enabled() && HCR_EL2.FB == '1' then
        if IsFeatureImplemented(FEAT_XS) &&
            IsFeatureImplemented(FEAT_HCX) && IsHCRXEL2Enabled()
            && HCRX_EL2.FnXS == '1' then
            AArch64.TLBI_VA(SecurityStateAtEL(EL1),
            Regime_EL10, VMID[], Shareability_ISH,
            TLBILevel_Any, TLBI_ExcludeXS, X[t, 64]);
        else
            AArch64.TLBI_VA(SecurityStateAtEL(EL1),
            Regime_EL10, VMID[], Shareability_ISH,
            TLBILevel_Any, TLBI_AllAttr, X[t, 64]);
```

```

else
    if IsFeatureImplemented(FEAT_XS) &&
        IsFeatureImplemented(FEAT_HCX) && IsHCRXEL2Enabled()
        && HCRX_EL2.FnXS == '1' then
        AArch64.TLBI_VA(SecurityStateAtEL(EL1),
            Regime_EL10, VMID[], Shareability_NSH,
            TLBILevel_Any, TLBI_ExcludeXS, X[t, 64]);
    else
        AArch64.TLBI_VA(SecurityStateAtEL(EL1),
            Regime_EL10, VMID[], Shareability_NSH,
            TLBILevel_Any, TLBI_AllAttr, X[t, 64]);
    elseif PSTATE.EL == EL2 then
        if HCR_EL2.<E2H,TGE> == '11' then
            AArch64.TLBI_VA(SecurityStateAtEL(EL2),
                Regime_EL20, VMID_NONE, Shareability_NSH,
                TLBILevel_Any, TLBI_AllAttr, X[t, 64]);
        else
            AArch64.TLBI_VA(SecurityStateAtEL(EL1),
                Regime_EL10, VMID[], Shareability_NSH,
                TLBILevel_Any, TLBI_AllAttr, X[t, 64]);
    elseif PSTATE.EL == EL3 then
        if HCR_EL2.<E2H,TGE> == '11' then
            AArch64.TLBI_VA(SecurityStateAtEL(EL2),
                Regime_EL20, VMID_NONE, Shareability_NSH,
                TLBILevel_Any, TLBI_AllAttr, X[t, 64]);
        else
            AArch64.TLBI_VA(SecurityStateAtEL(EL1),
                Regime_EL10, VMID[], Shareability_NSH,
                TLBILevel_Any, TLBI_AllAttr, X[t, 64]);

```

TLBI VAE1NXS{, <Xt>}

op0	op1	CRn	CRm	op2
0b01	0b000	0b1001	0b0111	0b001

```

if !IsFeatureImplemented(FEAT_XS) then
    UNDEFINED;
elseif PSTATE.EL == EL0 then
    UNDEFINED;
elseif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.TTLB == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elseif EL2Enabled() &&
        IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
        SCR_EL3.FGTEn == '1') &&
        IsFeatureImplemented(FEAT_HCX) && (!
        IsHCRXEL2Enabled() || HCRX_EL2.FGTnXS == '0') &&
        HFGITR_EL2.TLBIVAE1 == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elseif EL2Enabled() && HCR_EL2.FB == '1' then
        AArch64.TLBI_VA(SecurityStateAtEL(EL1),
            Regime_EL10, VMID[], Shareability_ISH,
            TLBILevel_Any, TLBI_ExcludeXS, X[t, 64]);

```

```

else
    AArch64.TLBI_VA(SecurityStateAtEL(EL1),
Regime_EL10, VMID[], Shareability_NSH,
TLBILevel_Any, TLBI_ExcludeXS, X[t, 64]);
elsif PSTATE.EL == EL2 then
    if HCR_EL2.<E2H,TGE> == '11' then
        AArch64.TLBI_VA(SecurityStateAtEL(EL2),
Regime_EL20, VMID_NONE, Shareability_NSH,
TLBILevel_Any, TLBI_ExcludeXS, X[t, 64]);
    else
        AArch64.TLBI_VA(SecurityStateAtEL(EL1),
Regime_EL10, VMID[], Shareability_NSH,
TLBILevel_Any, TLBI_ExcludeXS, X[t, 64]);
    elsif PSTATE.EL == EL3 then
        if HCR_EL2.<E2H,TGE> == '11' then
            AArch64.TLBI_VA(SecurityStateAtEL(EL2),
Regime_EL20, VMID_NONE, Shareability_NSH,
TLBILevel_Any, TLBI_ExcludeXS, X[t, 64]);
        else
            AArch64.TLBI_VA(SecurityStateAtEL(EL1),
Regime_EL10, VMID[], Shareability_NSH,
TLBILevel_Any, TLBI_ExcludeXS, X[t, 64]);

```

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

28/03/2023 16:01; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.