ID_PFR2_EL1, AArch32 Processor Feature Register 2

The ID_PFR2_EL1 characteristics are:

Purpose

Gives information about the AArch32 programmers' model.

Must be interpreted with ID_PFR0_EL1 and ID_PFR1_EL1.

For general information about the interpretation of the ID registers see 'Principles of the ID scheme for fields in ID registers'.

Configuration

AArch64 System register ID_PFR2_EL1 bits [31:0] are architecturally mapped to AArch32 System register ID_PFR2[31:0].

Attributes

ID_PFR2_EL1 is a 64-bit register.

Field descriptions

When AArch32 is supported:

63 62 61 60 59 58 57 56 55 54 53 52 51 50 49 48 47 46 45 44 43 42 41 40 39 38 37 36 35 34 33 32																															
RES0																															
31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12																11 10		9	8	7	6	5	4	3	2	1	0				
RES0																RAS_frac		SSBS						CSV3							

Bits [63:12]

Reserved, res0.

RAS_frac, bits [11:8]

RAS Extension fractional field. Defined values are:

RAS_frac	Meaning
0b0000	If ID_PFR0_EL1.RAS == 0b0001, RAS Extension implemented.

0b0001	If ID_PFR0_EL1.RAS == 0b0001, as 0b0000 and adds support for additional ERXMISC<m> System registers. Error records accessed through System registers conform to RAS System Architecture v1.1, which includes simplifications to ERR<n>STATUS and support for the optional RAS Timestamp Extension.

All other values are reserved.

This field is valid only if ID_PFR0_EL1.RAS == 0b0001.

SSBS, bits [7:4]

Speculative Store Bypassing controls in AArch64 state. Defined values are:

SSBS	Meaning
0b0000	AArch32 provides no mechanism to control the use of Speculative Store Bypassing.
0b0001	AArch32 provides the PSTATE.SSBS mechanism to mark regions that are Speculative Store Bypass Safe.

In Armv8.0, the permitted values are 0b0000 and 0b0001.

From Armv8.5, the only permitted value is 0b0001.

All other values are reserved.

CSV3, bits [3:0]

Speculative use of faulting data. Defined values are:

CSV3	Meaning

0b0000	This PE does not disclose whether data loaded under speculation with a permission or domain fault can be used to form an address or generate condition codes or SVE predicate values to be used by other instructions in the speculative sequence.
0b0001	Data loaded under speculation with a permission or domain fault cannot be used to form an address, generate condition codes, or generate SVE predicate values to be used by other instructions in the speculative sequence. The execution timing of any other instructions in the speculative sequence is not a function of the data loaded under speculation.

All other values are reserved.

FEAT_CSV3 implements the functionality identified by the value 0b0001.

In Armv8.0, the permitted values are 0b0000 and 0b0001.

From Armv8.5, the only permitted value is 0b0001.

If FEAT_E0PD is implemented, FEAT_CSV3 must be implemented.

Otherwise:

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
UNKNOWN																															
UNKNOWN																															
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0

Bits [63:0]

Reserved, unknown.

Accessing ID_PFR2_EL1

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, ID_PFR2_EL1

op0	op1	CRn	CRm	op2
0b11	0b000	0b0000	0b0011	0b100

```
if PSTATE.EL == EL0 then
    if IsFeatureImplemented(FEAT_IDST) then
        if EL2Enabled() && HCR_EL2.TGE == '1' then
            AArch64.SystemAccessTrap(EL2, 0x18);
        else
            AArch64.SystemAccessTrap(EL1, 0x18);
    else
        UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.TID3 == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    else
        X[t, 64] = ID_PFR2_EL1;
elsif PSTATE.EL == EL2 then
    X[t, 64] = ID_PFR2_EL1;
elsif PSTATE.EL == EL3 then
    X[t, 64] = ID_PFR2_EL1;
```

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94