

DBGCLAIMSET_EL1, Debug CLAIM Tag Set Register

The DBGCLAIMSET_EL1 characteristics are:

Purpose

Used by software to set the CLAIM tag bits to 1.

The architecture does not define any functionality for the CLAIM tag bits.

Note

CLAIM tags are typically used for communication between the debugger and target software.

Used in conjunction with the [DBGCLAIMCLR_EL1](#) register.

Configuration

AArch64 System register DBGCLAIMSET_EL1 bits [31:0] are architecturally mapped to AArch32 System register [DBGCLAIMSET\[31:0\]](#).

AArch64 System register DBGCLAIMSET_EL1 bits [31:0] are architecturally mapped to External register [DBGCLAIMSET_EL1\[31:0\]](#).

An implementation must include eight CLAIM tag bits.

Attributes

DBGCLAIMSET_EL1 is a 64-bit register.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
RES0																															
RAZ/WI																															
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
CLAIM																															

Bits [63:32]

Reserved, res0.

Bits [31:8]

Reserved, RAZ/WI.

CLAIM, bits [7:0]

Set CLAIM tag bits.

This field is RAO.

Writing a 1 to one of these bits sets the corresponding CLAIM tag bit to 1. This is an indirect write to the CLAIM tag bits. A single write operation can set multiple CLAIM tag bits to 1.

Writing 0 to one of these bits has no effect.

Accessing DBGCLAIMSET_EL1

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, DBGCLAIMSET_EL1

op0	op1	CRn	CRm	op2
0b10	0b000	0b0111	0b1000	0b110

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
    && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
    when SDD == '1'" && MDCR_EL3.TDA == '1' then
        UNDEFINED;
    elsif EL2Enabled() &&
    IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
    SCR_EL3.FGTEn == '1') && HDFGRTR_EL2.DBGCLAIM == '1'
    then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() && MDCR_EL2.<TDE,TDA> != '00'
    then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && MDCR_EL3.TDA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            X[t, 64] = DBGCLAIMSET_EL1;
    elsif PSTATE.EL == EL2 then
        if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
        && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
```

```

when SDD == '1' && MDCR_EL3.TDA == '1' then
    UNDEFINED;
elsif HaveEL(EL3) && MDCR_EL3.TDA == '1' then
    if Halted() && EDSCR.SDD == '1' then
        UNDEFINED;
    else
        AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = DBGCLAIMSET_EL1;
elsif PSTATE.EL == EL3 then
    X[t, 64] = DBGCLAIMSET_EL1;

```

MSR DBGCLAIMSET_EL1, <Xt>

op0	op1	CRn	CRm	op2
0b10	0b000	0b0111	0b1000	0b110

```

if PSTATE.EL == EL0 then
    UNDEFINED;
elseif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
    && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && MDCR_EL3.TDA == '1' then
        UNDEFINED;
    elseif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
SCR_EL3.FGTEn == '1') && HDFGWTR_EL2.DBGCLAIM == '1'
then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elseif EL2Enabled() && MDCR_EL2.<TDE,TDA> != '00'
then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elseif HaveEL(EL3) && MDCR_EL3.TDA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            DBGCLAIMSET_EL1 = X[t, 64];
elseif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
    && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && MDCR_EL3.TDA == '1' then
        UNDEFINED;
    elseif HaveEL(EL3) && MDCR_EL3.TDA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            DBGCLAIMSET_EL1 = X[t, 64];
elseif PSTATE.EL == EL3 then
    DBGCLAIMSET_EL1 = X[t, 64];

```

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

28/03/2023 16:01; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.