

BFDOT (multiple vectors)

Multi-vector BFloat16 floating-point dot-product

The instruction computes the dot product of a pair of BF16 values held in the corresponding 32-bit elements of the two or four first and second source vectors. The single-precision dot product results are destructively added to the corresponding single-precision elements of the ZA single-vector groups. The vector numbers forming the single-vector group within each half of or each quarter of the ZA array are selected by the sum of the vector select register and immediate offset, modulo half or quarter the number of ZA array vectors.

The vector group symbol, VGx2 or VGx4, indicates that the ZA operand consists of two or four ZA single-vector groups respectively. The vector group symbol is preferred for disassembly, but optional in assembler source code.

This instruction follows SME2 ZA-targeting BFloat16 numerical behaviors. This instruction is unpredicated.

It has encodings from 2 classes: [Two ZA single-vectors](#) and [Four ZA single-vectors](#)

Two ZA single-vectors (FEAT_SME2)

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	0	0	0	0	1	1	0	1	Zm			0	0	Rv	1	0	0	Zn			0	1	0	off3					

BFDOT ZA.S[<Wv>, <offs>{, VGx2}], { <Zn1>.H-<Zn2>.H }, { <Zm1>.H-<Zm2>.H }

```
if !HaveSME2() then UNDEFINED;
integer v = UInt('010':Rv);
integer n = UInt(Zn:'0');
integer m = UInt(Zm:'0');
integer offset = UInt(off3);
constant integer nreg = 2;
```

Four ZA single-vectors (FEAT_SME2)

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	0	0	0	0	1	1	0	1	Zm	0	1	0	Rv	1	0	0	Zn	0	0	1	0	off3							

BFDOT ZA.S[<Wv>, <offs>{, VGx4}], { <Zn1>.H-<Zn4>.H }, { <Zm1>.H-<Zm4>.H }

```
if !HaveSME2() then UNDEFINED;
integer v = UInt('010':Rv);
integer n = UInt(Zn:'00');
integer m = UInt(Zm:'00');
integer offset = UInt(off3);
constant integer nreg = 4;
```

Assembler Symbols

<Wv>	Is the 32-bit name of the vector select register W8-W11, encoded in the "Rv" field.
<offs>	Is the vector select offset, in the range 0 to 7, encoded in the "off3" field.
<Zn1>	<p>For the two ZA single-vectors variant: is the name of the first scalable vector register of a multi-vector sequence, encoded as "Zn" times 2.</p> <p>For the four ZA single-vectors variant: is the name of the first scalable vector register of a multi-vector sequence, encoded as "Zn" times 4.</p>
<Zn4>	Is the name of the fourth scalable vector register of a multi-vector sequence, encoded as "Zn" times 4 plus 3.
<Zn2>	Is the name of the second scalable vector register of a multi-vector sequence, encoded as "Zn" times 2 plus 1.
<Zm1>	<p>For the two ZA single-vectors variant: is the name of the first scalable vector register of a multi-vector sequence, encoded as "Zm" times 2.</p> <p>For the four ZA single-vectors variant: is the name of the first scalable vector register of a multi-vector sequence, encoded as "Zm" times 4.</p>
<Zm4>	Is the name of the fourth scalable vector register of a multi-vector sequence, encoded as "Zm" times 4 plus 3.
<Zm2>	Is the name of the second scalable vector register of a multi-vector sequence, encoded as "Zm" times 2 plus 1.

Operation

```
CheckStreamingSVEAndZAAEnabled();
constant integer VL = CurrentVL;
constant integer elements = VL DIV 32;
integer vectors = VL DIV 8;
integer vstride = vectors DIV nreg;
bits(32) vbase = X[v, 32];
integer vec = (UInt(vbase) + offset) MOD vstride;
bits(VL) result;

for r = 0 to nreg-1
    bits(VL) operand1 = Z[n+r, VL];
    bits(VL) operand2 = Z[m+r, VL];
    bits(VL) operand3 = ZAvector[vec, VL];
    for e = 0 to elements-1
        bits(16) elt1_a = Elem[operand1, 2 * e + 0, 16];
        bits(16) elt1_b = Elem[operand1, 2 * e + 1, 16];
        bits(16) elt2_a = Elem[operand2, 2 * e + 0, 16];
        bits(16) elt2_b = Elem[operand2, 2 * e + 1, 16];
        bits(32) sum = Elem[operand3, e, 32];
```

```
sum = BFDotAdd(sum, elt1_a, elt1_b, elt2_a, elt2_b, FPCR[]);  
Elem[result, e, 32] = sum;  
ZAvector[vec, VL] = result;  
vec = vec + vstride;
```

[Base
Instructions](#)

[SIMD&FP
Instructions](#)

[SVE
Instructions](#)

[SME
Instructions](#)

[Index by
Encoding](#)

[Sh
Pseudocode](#)

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode
no_diffs_2023_09_RC2, sve v2023-06_rel ; Build timestamp: 2023-09-18T17:56

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This
document is Non-Confidential.