<u>ex by</u>	<u>Sh</u>
oding	<u>Pseuc</u>

BaseSIMD&FPSVESMEIndex byInstructionsInstructionsInstructionsInstructionsEncoding

MSUB

Multiply-Subtract multiplies two register values, subtracts the product from a third register value, and writes the result to the destination register. This instruction is used by the alias MNEG.

31 30 29 28 2	27 26	25 24	23	22 2	L 20 19 18 17 16	15	14 13 12 11 10	9	8 7	6	5	4	3	2	1	0
sf 0 0 1	1 0	1 1	0	0 0	Rm	1	Ra		Rr	1				Rd		
00																

```
32-bit (sf == 0)
```

```
MSUB <Wd>, <Wn>, <Wm>, <Wa>

64-bit (sf == 1)

MSUB <Xd>, <Xn>, <Xm>, <Xa>

integer d = UInt(Rd);
integer n = UInt(Rn);
integer m = UInt(Rm);
integer a = UInt(Rm);
constant integer destsize = 32 << UInt(sf);</pre>
```

Assembler Symbols

<wd></wd>	Is the 32-bit name of the general-purpose destination register, encoded in the "Rd" field.
<wn></wn>	Is the 32-bit name of the first general-purpose source register holding the multiplicand, encoded in the "Rn" field.
<wm></wm>	Is the 32-bit name of the second general-purpose source register holding the multiplier, encoded in the "Rm" field.
<wa></wa>	Is the 32-bit name of the third general-purpose source register holding the minuend, encoded in the "Ra" field.
<xd></xd>	Is the 64-bit name of the general-purpose destination register, encoded in the "Rd" field.
<xn></xn>	Is the 64-bit name of the first general-purpose source register holding the multiplicand, encoded in the "Rn" field.
<xm></xm>	Is the 64-bit name of the second general-purpose source register holding the multiplier, encoded in the "Rm" field.
<xa></xa>	Is the 64-bit name of the third general-purpose source register holding the minuend, encoded in the "Ra" field.

Alias Conditions

Alias	Is preferred when			
MNEG	Ra == '11111'			

Operation

```
bits(destsize) operand1 = X[n, destsize];
bits(destsize) operand2 = X[m, destsize];
bits(destsize) operand3 = X[a, destsize];
integer result;

result = UInt(operand3) - (UInt(operand1) * UInt(operand2));
X[d, destsize] = result<destsize-1:0>;
```

Operational information

If PSTATE.DIT is 1:

- The execution time of this instruction is independent of:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.
- The response of this instruction to asynchronous exceptions does not vary based on:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.

<u>Base</u>	SIMD&FP	<u>SVE</u>	<u>SME</u>	<u>Index by</u>
<u>Instructions</u>	<u>Instructions</u>	<u>Instructions</u>	<u>Instructions</u>	Encoding

 $Internal\ version\ only:\ is a\ v33.64,\ AdvSIMD\ v29.12,\ pseudocode\ no_diffs_2023_09_RC2,\ sve\ v2023-06_rel\ ;\ Build\ timestamp:\ 2023-09-18T17:56$

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.

Sh Pseu