

CPYPRN, CPYMRN, CPYERN

Memory Copy, reads non-temporal. These instructions perform a memory copy. The prologue, main, and epilogue instructions are expected to be run in succession and to appear consecutively in memory: CPYPRN, then CPYMRN, and then CPYERN.

CPYPRN performs some preconditioning of the arguments suitable for using the CPYMRN instruction, and performs an implementation defined amount of the memory copy. CPYMRN performs an implementation defined amount of the memory copy. CPYERN performs the last part of the memory copy.

Note

The inclusion of implementation defined amounts of memory copy allows some optimization of the size that can be performed.

For CPYPRN, the following saturation logic is applied:

If $X_n < 63:55 > \neq 00000000$, the copy size X_n is saturated to $0x007FFFFFFFFFFFFFFF$.

After that saturation logic is applied, the direction of the memory copy is based on the following algorithm:

If $(X_s > X_d) \ \&\& \ (X_d + \text{saturated } X_n) > X_s$, then direction = forward
Elsif $(X_s < X_d) \ \&\& \ (X_s + \text{saturated } X_n) > X_d$, then direction = backward
Else direction = implementation defined choice between forward and backward.

The architecture supports two algorithms for the memory copy: option A and option B. Which algorithm is used is implementation defined.

Note

Portable software should not assume that the choice of algorithm is constant.

After execution of CPYPRN, option A (which results in encoding $PSTATE.C = 0$):

- $PSTATE.\{N,Z,V\}$ are set to $\{0,0,0\}$.
- If the copy is in the forward direction, then:
 - X_s holds the original $X_s + \text{saturated } X_n$.
 - X_d holds the original $X_d + \text{saturated } X_n$.
 - X_n holds $-1 * \text{saturated } X_n + \text{an implementation defined number of bytes copied}$.
- If the copy is in the backward direction, then:
 - X_s and X_d are unchanged.
 - X_n holds the saturated value of $X_n - \text{an implementation defined number of bytes copied}$.

After execution of CPYPRN, option B (which results in encoding PSTATE.C = 1):

- If the copy is in the forward direction, then:
 - Xs holds the original Xs + an implementation defined number of bytes copied.
 - Xd holds the original Xd + an implementation defined number of bytes copied.
 - Xn holds the saturated Xn - an implementation defined number of bytes copied.
 - PSTATE.{N,Z,V} are set to {0,0,0}.
- If the copy is in the backward direction, then:
 - Xs holds the original Xs + saturated Xn - an implementation defined number of bytes copied.
 - Xd holds the original Xd + saturated Xn - an implementation defined number of bytes copied.
 - Xn holds the saturated Xn - an implementation defined number of bytes copied.
 - PSTATE.{N,Z,V} are set to {1,0,0}.

For CPYMRN, option A (encoded by PSTATE.C = 0), the format of the arguments is:

- Xn is treated as a signed 64-bit number.
- If the copy is in the forward direction (Xn is a negative number), then:
 - Xn holds -1* the number of bytes remaining to be copied in the memory copy in total.
 - Xs holds the lowest address that the copy is copied from - Xn.
 - Xd holds the lowest address that the copy is made to - Xn.
 - At the end of the instruction, the value of Xn is written back with -1* the number of bytes remaining to be copied in the memory copy in total.
- If the copy is in the backward direction (Xn is a positive number), then:
 - Xn holds the number of bytes remaining to be copied in the memory copy in total.
 - Xs holds the highest address that the copy is copied from - Xn+1.
 - Xd holds the highest address that the copy is copied to - Xn+1.
 - At the end of the instruction, the value of Xn is written back with the number of bytes remaining to be copied in the memory copy in total.

For CPYMRN, option B (encoded by PSTATE.C = 1), the format of the arguments is:

- Xn holds the number of bytes to be copied in the memory copy in total.

- If the copy is in the forward direction ($PSTATE.N == 0$), then:
 - Xs holds the lowest address that the copy is copied from.
 - Xd holds the lowest address that the copy is copied to.
 - At the end of the instruction:
 - the value of Xn is written back with the number of bytes remaining to be copied in the memory copy in total.
 - the value of Xs is written back with the lowest address that has not been copied from.
 - the value of Xd is written back with the lowest address that has not been copied to.
- If the copy is in the backward direction ($PSTATE.N == 1$), then:
 - Xs holds the highest address that the copy is copied from +1.
 - Xd holds the highest address that the copy is copied to +1.
 - At the end of the instruction:
 - the value of Xn is written back with the number of bytes remaining to be copied in the memory copy in total.
 - the value of Xs is written back with the highest address that has not been copied from +1.
 - the value of Xd is written back with the highest address that has not been copied to +1.

For CPYERN, option A (encoded by $PSTATE.C = 0$), the format of the arguments is:

- Xn is treated as a signed 64-bit number.
- If the copy is in the forward direction (Xn is a negative number), then:
 - Xn holds $-1 \times$ the number of bytes remaining to be copied in the memory copy in total.
 - Xs holds the lowest address that the copy is copied from - Xn.
 - Xd holds the lowest address that the copy is made to -Xn.
 - At the end of the instruction, the value of Xn is written back with 0.
- If the copy is in the backward direction (Xn is a positive number), then:
 - Xn holds the number of bytes remaining to be copied in the memory copy in total.
 - Xs holds the highest address that the copy is copied from - Xn+1.
 - Xd holds the highest address that the copy is copied to - Xn+1.
 - At the end of the instruction, the value of Xn is written back with 0.

For CPYERN, option B (encoded by PSTATE.C = 1), the format of the arguments is:

- Xn holds the number of bytes to be copied in the memory copy in total.
- If the copy is in the forward direction (PSTATE.N == 0), then:
 - Xs holds the lowest address that the copy is copied from.
 - Xd holds the lowest address that the copy is copied to.
 - At the end of the instruction:
 - the value of Xn is written back with 0.
 - the value of Xs is written back with the lowest address that has not been copied from.
 - the value of Xd is written back with the lowest address that has not been copied to.
- If the copy is in the backward direction (PSTATE.N == 1), then:
 - Xs holds the highest address that the copy is copied from +1.
 - Xd holds the highest address that the copy is copied to +1.
 - At the end of the instruction:
 - the value of Xn is written back with 0.
 - the value of Xs is written back with the highest address that has not been copied from +1.
 - the value of Xd is written back with the highest address that has not been copied to +1.

Integer (FEAT_MOPS)

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
sz		0	1	1	1	0	1	op1		0	Rs				1 0 0 0				0 1		Rn				Rd						
																op2															

Epilogue (op1 == 10)

CPYERN [[<Xd>](#)]!, [[<Xs>](#)]!, [<Xn>](#)!

Main (op1 == 01)

CPYMRN [[<Xd>](#)]!, [[<Xs>](#)]!, [<Xn>](#)!

Prologue (op1 == 00)

CPYPRN [[<Xd>](#)]!, [[<Xs>](#)]!, [<Xn>](#)!

```
if !IsFeatureImplemented(FEAT_MOPS) || sz != '00' then UNDEFINED;

integer d = UInt(Rd);
integer s = UInt(Rs);
integer n = UInt(Rn);
bits(4) options = op2;
boolean rntemporal = options<3> == '1';
boolean wntemporal = options<2> == '1';
```

```

MOPSSStage stage;
case op1 of
    when '00' stage = MOPSSStage_Prologue;
    when '01' stage = MOPSSStage_Main;
    when '10' stage = MOPSSStage_Epilogue;
    otherwise SEE "Memory Copy and Memory Set";

CheckMOPSEnabled();

if s == n || s == d || n == d || d == 31 || s == 31 || n == 31 then
    Constraint c = ConstrainUnpredictable(Unpredictable_MOPSOVERLAP31);
    assert c IN {Constraint_UNDEF, Constraint_NOP};
    case c of
        when Constraint_UNDEF UNDEFINED;
        when Constraint_NOP EndOfInstruction();

```

For information about the constrained unpredictable behavior of this instruction, see *Architectural Constraints on UNPREDICTABLE behaviors*, and particularly *Memory Copy and Memory Set CPY**.

Assembler Symbols

- <Xd> For the epilogue and main variant: is the 64-bit name of the general-purpose register that holds an encoding of the destination address, encoded in the "Rd" field.
- For the prologue variant: is the 64-bit name of the general-purpose register that holds the destination address and is updated by the instruction, encoded in the "Rd" field.
- <Xs> For the epilogue and main variant: is the 64-bit name of the general-purpose register that holds an encoding of the source address, encoded in the "Rs" field.
- For the prologue variant: is the 64-bit name of the general-purpose register that holds the source address and is updated by the instruction, encoded in the "Rs" field.
- <Xn> For the epilogue variant: is the 64-bit name of the general-purpose register that holds an encoding of the number of bytes to be transferred and is set to zero at the end of the instruction, encoded in the "Rn" field.
- For the main variant: is the 64-bit name of the general-purpose register that holds an encoding of the number of bytes to be transferred, encoded in the "Rn" field.
- For the prologue variant: is the 64-bit name of the general-purpose register that holds the number of bytes to be transferred and is updated by the instruction to encode the remaining size and destination, encoded in the "Rn" field.

Operation

```

constant integer N = MaxBlockSizeCopiedBytes();
bits(64) toaddress = X[d, 64];
bits(64) fromaddress = X[s, 64];
bits(64) cpysize = X[n, 64];
bits(4) nzcv = PSTATE.<N,Z,C,V>;
bits(8*N) readdata;

boolean implements_option_a = CPYOptionA();
boolean rprivileged = if options<1> == '1' then AArch64.IsUnprivAccessP
boolean wprivileged = if options<0> == '1' then AArch64.IsUnprivAccessP

AccessDescriptor raccdesc = CreateAccDescMOPS(MemOp\_LOAD, rprivileged,
AccessDescriptor waccdesc = CreateAccDescMOPS(MemOp\_STORE, wprivileged,

if stage == MOPSTage\_Prologue then
    if cpysize<63:55> != '000000000' then cpysize = 0x007FFFFFFFFFFFFFFF<

    boolean forward = IsMemCpyForward(toaddress, fromaddress, cpysize);

    if implements_option_a then
        nzcv = '0000';
        if forward then
            // Copy in the forward direction offsets the arguments.
            toaddress = toaddress + cpysize;
            fromaddress = fromaddress + cpysize;
            cpysize = Zeros(64) - cpysize;
        else
            if !forward then
                // Copy in the reverse direction offsets the arguments.
                toaddress = toaddress + cpysize;
                fromaddress = fromaddress + cpysize;
                nzcv = '1010';
            else
                nzcv = '0010';
        else
            CheckMemCpyParams(stage, implements_option_a, nzcv, options, d, s,

bits(64) stagecpysize = MemCpyStageSize(stage, toaddress, fromaddress,

if implements_option_a then
    while SInt(stagecpysize) != 0 do
        // IMP DEF selection of the block size that is worked on. While
        // implementations might make this constant, that is not assume
        constant integer B = CPYSizeChoice(toaddress, fromaddress, cpy

        if SInt(cpysize) < 0 then
            assert B <= -1 * SInt(stagecpysize);

            readdata<B*8-1:0> = Mem[fromaddress+cpysize, B, raccdesc];
            Mem[toaddress+cpysize, B, waccdesc] = readdata<B*8-1:0>;

            cpysize = cpysize + B;
            stagecpysize = stagecpysize + B;
        else
            assert B <= SInt(stagecpysize);
            cpysize = cpysize - B;
            stagecpysize = stagecpysize - B;

            readdata<B*8-1:0> = Mem[fromaddress+cpysize, B, raccdesc];
            Mem[toaddress+cpysize, B, waccdesc] = readdata<B*8-1:0>;

```

```

        if stage != MOPSSStage\_Prologue then
            X[n, 64] = cpysize;
else
    while UInt(stagecpysize) > 0 do
        // IMP DEF selection of the block size that is worked on. While
        // implementations might make this constant, that is not assume
        constant integer B = CPYSizeChoice(toaddress, fromaddress, cpys
        assert B <= UInt(stagecpysize);

        if nzcvc<3> == '0' then // PSTATE.N
            readdata<B*8-1:0> = Mem[fromaddress, B, raccdesc];
            Mem[toaddress, B, waccdesc] = readdata<B*8-1:0>;

            fromaddress = fromaddress + B;
            toaddress = toaddress + B;
        else
            readdata<B*8-1:0> = Mem[fromaddress-B, B, raccdesc];
            Mem[toaddress-B, B, waccdesc] = readdata<B*8-1:0>;

            fromaddress = fromaddress - B;
            toaddress = toaddress - B;

        cpysize = cpysize - B;
        stagecpysize = stagecpysize - B;

        if stage != MOPSSStage\_Prologue then
            X[n, 64] = cpysize;
            X[d, 64] = toaddress;
            X[s, 64] = fromaddress;

if stage == MOPSSStage\_Prologue then
    X[n, 64] = cpysize;
    X[d, 64] = toaddress;
    X[s, 64] = fromaddress;
    PSTATE.<N,Z,C,V> = nzcvc;

```

[Base
Instructions](#)

[SIMD&FP
Instructions](#)

[SVE
Instructions](#)

[SME
Instructions](#)

[Index by
Encoding](#)

[Sh
Pseud](#)

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode
no_diffs_2023_09_RC2, sve v2023-06_rel ; Build timestamp: 2023-09-18T17:56

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This
document is Non-Confidential.