AArch32 Instructions AArch64 Instructions Index by Encoding

External Registers

TRCCCCTLR, Cycle Count Control Register

The TRCCCCTLR characteristics are:

Purpose

Set the threshold value for cycle counting.

Configuration

AArch64 System register TRCCCCTLR bits [31:0] are architecturally mapped to External register TRCCCCTLR[31:0].

This register is present only when FEAT_ETE is implemented, FEAT_TRC_SR is implemented and TRCIDR0.TRCCCI == 1. Otherwise, direct accesses to TRCCCCTLR are undefined.

Attributes

TRCCCCTLR is a 64-bit register.

Field descriptions

63 62 61 60 59 58 57 56 55 54 53 52 51 50 49 48 47 46 45 44 43 42 41 40 39 38 37 36 35 34 33 32

RES0			
RES0	THRESHOLD		
31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12	1110 9 8 7 6 5 4 3 2 1 0		

Bits [63:12]

Reserved, res0.

THRESHOLD, bits [11:0]

Sets the threshold value for instruction trace cycle counting.

The minimum threshold value that can be programmed into THRESHOLD is given in TRCIDR3. CCITMIN. If the THRESHOLD value is smaller than the value in TRCIDR3. CCITMIN then the behavior is constrained unpredictable. That is, cycle counts might or might not be included in the trace and the cycle count threshold is not known.

Writing a value of zero when <u>TRCCONFIGR</u>.CCI enables instruction trace cycle counting results in constrained unpredictable behavior. That is, cycle counts might or might not be included in the trace and the cycle count threshold is not known.

The reset behavior of this field is:

• On a Trace unit reset, this field resets to an architecturally unknown value.

Accessing TRCCCCTLR

Must be programmed if $\underline{TRCCONFIGR}$.CCI == 1.

Writes are constrained unpredictable if the trace unit is not in the Idle state.

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, TRCCCCTLR

op0	op1	CRn	CRm	op2
0b10	0b001	0b0000	0b1110	0b000

```
if PSTATE.EL == ELO then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
    elsif CPACR EL1.TTA == '1' then
        AArch64.SystemAccessTrap(EL1, 0x18);
    elsif EL2Enabled() && CPTR_EL2.TTA == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) | |
SCR_EL3.FGTEn == '1') && HDFGRTR_EL2.TRC == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = TRCCCCTLR;
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
```

MSR TRCCCCTLR, <Xt>

op0	op1	CRn	CRm	op2
0b10	0b001	0b0000	0b1110	0b000

```
if PSTATE.EL == ELO then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
    elsif CPACR_EL1.TTA == '1' then
        AArch64.SystemAccessTrap(EL1, 0x18);
    elsif EL2Enabled() && CPTR_EL2.TTA == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) | |
SCR_EL3.FGTEn == '1') && HDFGWTR_EL2.TRC == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
        TRCCCCTLR = X[t, 64];
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
    elsif CPTR EL2.TTA == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
```

```
AArch64.SystemAccessTrap(EL3, 0x18);
else
    TRCCCCTLR = X[t, 64];
elsif PSTATE.EL == EL3 then
    if CPTR_EL3.TTA == '1' then
        AArch64.SystemAccessTrap(EL3, 0x18);
else
    TRCCCCTLR = X[t, 64];
```

AArch32 Registers AArch64 Registers

AArch32 Instructions AArch64 Instructions

Index by Encoding

External Registers

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright \hat{A} © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.