TRCTSCTLR, Timestamp Control Register

The TRCTSCTLR characteristics are:

Purpose

Controls the insertion of global timestamps in the trace stream.

Configuration

AArch64 System register TRCTSCTLR bits [31:0] are architecturally mapped to External register TRCTSCTLR[31:0].

This register is present only when FEAT_ETE is implemented, FEAT_TRC_SR is implemented and TRCIDR0.TSSIZE != 0b00000. Otherwise, direct accesses to TRCTSCTLR are undefined.

Attributes

TRCTSCTLR is a 64-bit register.

Field descriptions

63 62 61 60 59 58 57 56 55 54 53 52 51 50 49 48 47 46 45 44 43 42 41 40	39	38 37 36 35 34 33 32
RES0		

31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8	7	6 5	4 3 2 1 0
RES0	EVENT_TYPE	RES0	EVENT_SEL

Bits [63:8]

Reserved, res0.

EVENT_TYPE, bit [7]
When TRCIDR4.NUMRSPAIR != 0b0000:

Chooses the type of Resource Selector.

EVENT_TYPE	Meaning
0b0	A single Resource Selector. TRCTSCTLR.EVENT.SEL[4:0] selects the single Resource Selector, from 0-31, used to activate the resource event.

| | 0b1 | A Boolean-combined pair of Resource Selectors. TRCTSCTLR.EVENT.SEL[3:0] selects the Resource Selector pair, from 0-15, that has a Boolean function that is applied to it whose output is used to activate the resource event. TRCTSCTLR.EVENT.SEL[4] is res0. |

The reset behavior of this field is:

- On a Trace unit reset, this field resets to an architecturally unknown value.

Otherwise:

Reserved, res0.

Bits [6:5]

Reserved, res0.

EVENT_SEL, bits [4:0]
When TRCIDR4.NUMRSPAIR != 0b0000:

Defines the selected Resource Selector or pair of Resource Selectors. TRCTSCTLR.EVENT.TYPE controls whether TRCTSCTLR.EVENT.SEL is the index of a single Resource Selector, or the index of a pair of Resource Selectors.

If an unimplemented Resource Selector is selected using this field, the behavior of the resource event is unpredictable, and the resource event might fire or might not fire when the resources are not in the Paused state.

Selecting Resource Selector pair 0 using this field is unpredictable, and the resource event might fire or might not fire when the resources are not in the Paused state.

The reset behavior of this field is:

- On a Trace unit reset, this field resets to an architecturally unknown value.

Otherwise:

Reserved, res0.

Accessing TRCTSCTLR

Must be programmed if [TRCCONFIGR](#).TS == 1.

Writes are constrained unpredictable if the trace unit is not in the Idle state.

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, TRCTSCTLR

op0	op1	CRn	CRm	op2
0b10	0b001	0b0000	0b1100	0b000

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
    elsif CPACR_EL1.TTA == '1' then
        AArch64.SystemAccessTrap(EL1, 0x18);
    elsif EL2Enabled() && CPTR_EL2.TTA == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
SCR_EL3.FGTEn == '1') && HDFGRTR_EL2.TRC == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = TRCTSCTLR;
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
    elsif CPTR_EL2.TTA == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = TRCTSCTLR;
elsif PSTATE.EL == EL3 then
    if CPTR_EL3.TTA == '1' then
```

```
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            X[t, 64] = TRCTSCTLR;
```

MSR TRCTSCTLR, <Xt>

op0	op1	CRn	CRm	op2
0b10	0b001	0b0000	0b1100	0b000

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
    elsif CPACR_EL1.TTA == '1' then
        AArch64.SystemAccessTrap(EL1, 0x18);
    elsif EL2Enabled() && CPTR_EL2.TTA == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
SCR_EL3.FGTEn == '1') && HDFGWTR_EL2.TRC == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        TRCTSCTLR = X[t, 64];
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
    elsif CPTR_EL2.TTA == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        TRCTSCTLR = X[t, 64];
elsif PSTATE.EL == EL3 then
    if CPTR_EL3.TTA == '1' then
        AArch64.SystemAccessTrap(EL3, 0x18);
    else
        TRCTSCTLR = X[t, 64];
```

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94