<u>Base</u>	SIMD&FP	<u>SVE</u>	<u>SME</u>	Index by
<u>Instructions</u>	<u>Instructions</u>	<u>Instructions</u>	<u>Instructions</u>	Encoding

Pseu

AESMC

AES mix columns

The AESMC instruction reads a 16-byte state array from each 128-bit segment of the source register, and performs a single round of the mixcolumns() transformation on each state array in accordance with the AES standard. Each updated state array is destructively placed in the corresponding segment of the first source vector. This instruction is unpredicated. ID_AA64ZFR0_EL1.AES indicates whether this instruction is implemented. This instruction is illegal when executed in Streaming SVE mode, unless FEAT SME FA64 is implemented and enabled.

```
SVE2 (FEAT_SVE_AES)
```

```
AESMC <Zdn>.B, <Zdn>.B

if !HaveSVE() | !HaveSVE2AES() then UNDEFINED;
integer dn = UInt(Zdn);
```

Assembler Symbols

<Zdn>

Is the name of the source and destination scalable vector register, encoded in the "Zdn" field.

Operation

Operational information

If PSTATE.DIT is 1:

- The execution time of this instruction is independent of:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.

- The response of this instruction to asynchronous exceptions does not vary based on:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.

<u>Base SIMD&FP SVE SME Index by Instructions Instructions Instructions Encoding</u>

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode no diffs 2023 09 RC2, sve v2023-06 rel; Build timestamp: 2023-09-18T17:56

Copyright \hat{A} © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.

Sh Pseu