

MPAMCFG_MBW_PBM<n>, MPAM Bandwidth Portion Bitmap Partition Configuration Register, n = 0 - 127

The MPAMCFG_MBW_PBM<n> characteristics are:

Purpose

The MPAMCFG_MBW_PBM<n> register array gives access to the memory bandwidth portion bitmap. Each register in the array is a read/write register that configures whether a PARTID is allowed to allocate bandwidth portions within a range.

The range of portions covered in MPAMCFG_MBW_PBM<n> is from portion <32*n> to portion <32*n + 31>.

After setting [MPAMCFG_PART_SEL](#) with a PARTID, software writes to one or more of the MPAMCFG_MBW_PBM<n> registers to configure with bandwidth portions the PARTID is allowed to allocate.

The MPAMCFG_MBW_PBM<n> register that contains the bitmap bit corresponding to memory bandwidth portion p has n equal to p[11:5]. The field, P<x> of that MPAMCFG_MBW_PBM<n> register that contains the bitmap bit corresponding to memory bandwidth portion p has <x> equal to p[4:0].

The MPAMCFG_MBW_PBM<n>_s registers control the bandwidth portion bitmap for the Secure PARTID selected by the Secure instance of [MPAMCFG_PART_SEL](#). The MPAMCFG_MBW_PBM<n>_ns registers control the bandwidth portion bitmap for the Non-secure PARTID selected by the Non-secure instance of [MPAMCFG_PART_SEL](#). The MPAMCFG_MBW_PBM<n>_rt registers control the bandwidth portion bitmap for the Root PARTID selected by the Root instance of [MPAMCFG_PART_SEL](#). The MPAMCFG_MBW_PBM<n>_rl registers control the bandwidth portion bitmap for the Realm PARTID selected by the Realm instance of [MPAMCFG_PART_SEL](#).

If [MPAMF_IDR](#).HAS_RIS is 1, the control settings accessed are those of the resource instance currently selected by [MPAMCFG_PART_SEL](#).RIS and the PARTID selected by [MPAMCFG_PART_SEL](#).PARTID_SEL.

Configuration

This register is present only when FEAT_MPAM is implemented, MPAMF_IDR.HAS_MBW_PART == 1 and MPAMF_MBW_IDR.HAS_PBM

== 1. Otherwise, direct accesses to MPAMCFG_MBW_PBM<n> are RES0.

The power and reset domain of each MSC component is specific to that component.

Attributes

MPAMCFG_MBW_PBM<n> is a 32-bit register.

Field descriptions

| | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|----|----|----|
| 31 | 30 | 29 | 28 | 27 | 26 | 25 | 24 | 23 | 22 | 21 | 20 | 19 | 18 | 17 | 16 | 15 | 14 | 13 | 12 | 11 | 10 | 9 | 8 | 7 | 6 | 5 | 4 |
| P31 | P30 | P29 | P28 | P27 | P26 | P25 | P24 | P23 | P22 | P21 | P20 | P19 | P18 | P17 | P16 | P15 | P14 | P13 | P12 | P11 | P10 | P9 | P8 | P7 | P6 | P5 | P4 |

P<x>, bit [x], for x = 31 to 0

Portion allocation control bit. Each bandwidth portion allocation control bit MPAMCFG_MBW_PBM<n>.P<x> grants permission to the PARTID selected by [MPAMCFG_PART_SEL](#) to allocate bandwidth within bandwidth portion <32*n> + <x>.

| P<x> | Meaning |
|------|--|
| 0b0 | The PARTID is not permitted to allocate into bandwidth portion <32*n> + <x>. |
| 0b1 | The PARTID is permitted to allocate within bandwidth portion <32*n> + <x>. |

The number of bits in the bandwidth portion partitioning bit map of this component is given in [MPAMF_MBW_IDR.BWPBM_WD](#).

BWPBM_WD contains a value from 1 to 2¹², inclusive. Values of [MPAMF_MBW_IDR.BWPBM_WD](#) greater than 32 require a group of 32-bit registers to access the bandwidth portion bitmap, up to 128 32-bit registers.

When (n * 32) + x > UInt(MPAMF_MBW_IDR.BWPBM_WD), access to this field is **RES0**.

Accessing MPAMCFG_MBW_PBM<n>

This register is within the MPAM feature page memory frames.

In a system that supports Secure, Non-secure, Root, and Realm memory maps, there must be MPAM feature pages in all four address maps:

- MPAMCFG_MBW_PBM<n>_s must only be accessible from the Secure MPAM feature page.
- MPAMCFG_MBW_PBM<n>_ns must only be accessible from the Non-secure MPAM feature page.

- MPAMCFG_MBW_PBM<n>_rt must only be accessible from the Root MPAM feature page.
- MPAMCFG_MBW_PBM<n>_rl must only be accessible from the Realm MPAM feature page.

MPAMCFG_MBW_PBM<n>_s, MPAMCFG_MBW_PBM<n>_ns, MPAMCFG_MBW_PBM<n>_rt, and MPAMCFG_MBW_PBM<n>_rl must be separate registers:

- The Secure instance (MPAMCFG_MBW_PBM<n>_s) accesses the memory bandwidth portion bitmap used for Secure PARTIDs.
- The Non-secure instance (MPAMCFG_MBW_PBM<n>_ns) accesses the memory bandwidth portion bitmap used for Non-secure PARTIDs.
- The Root instance (MPAMCFG_MBW_PBM<n>_rt) accesses the memory bandwidth portion bitmap used for Root PARTIDs.
- The Realm instance (MPAMCFG_MBW_PBM<n>_rl) accesses the memory bandwidth portion bitmap used for Realm PARTIDs.

When RIS is implemented, loads and stores to MPAMCFG_MBW_PBM<n> access the memory bandwidth portion bitmap configuration settings for the bandwidth resource instance selected by [MPAMCFG_PART_SEL](#).RIS and the PARTID selected by [MPAMCFG_PART_SEL](#).PARTID_SEL.

When RIS is not implemented, loads and stores to MPAMCFG_MBW_PBM<n> access the memory bandwidth portion bitmap configuration settings for the PARTID selected by [MPAMCFG_PART_SEL](#).PARTID_SEL.

When PARTID narrowing is implemented, loads and stores to MPAMCFG_MBW_PBM<n> access the memory bandwidth portion bitmap configuration settings for the internal PARTID selected by [MPAMCFG_PART_SEL](#).PARTID_SEL, and [MPAMCFG_PART_SEL](#).INTERNAL must be 1.

When PARTID narrowing is not implemented, loads and stores to MPAMCFG_MBW_PBM<n> access the memory bandwidth portion bitmap configuration settings for the request PARTID selected by [MPAMCFG_PART_SEL](#).PARTID_SEL, and [MPAMCFG_PART_SEL](#).INTERNAL must be 0.

MPAMCFG_MBW_PBM<n> can be accessed through the memory-mapped interfaces:

| Component | Frame | Offset | Instance |
|-----------|--------------|------------------------|----------------------|
| MPAM | MPAMF_BASE_s | 0x2000 + (4 * n) | MPAMCFG_MBW_PBM<n>_s |

Accesses on this interface are **RW**.

| Component | Frame | Offset | Instance |
|-----------|---------------|------------------------|-----------------------|
| MPAM | MPAMF_BASE_ns | 0x2000 + (4 * n) | MPAMCFG_MBW_PBM<n>_ns |

Accesses on this interface are **RW**.

| Component | Frame | Offset | Instance |
|-----------|---------------|------------------------|-----------------------|
| MPAM | MPAMF_BASE_rt | 0x2000 + (4 * n) | MPAMCFG_MBW_PBM<n>_rt |

When FEAT_RME is implemented, accesses on this interface are **RW**.

| Component | Frame | Offset | Instance |
|-----------|---------------|------------------------|-----------------------|
| MPAM | MPAMF_BASE_rl | 0x2000 + (4 * n) | MPAMCFG_MBW_PBM<n>_rl |

When FEAT_RME is implemented, accesses on this interface are **RW**.

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.