DACR32_EL2, Domain Access Control Register

The DACR32_EL2 characteristics are:

Purpose

Allows access to the AArch32 DACR register from AArch64 state only. Its value has no effect on execution in AArch64 state.

Configuration

AArch64 System register DACR32_EL2 bits [31:0] are architecturally mapped to AArch32 System register DACR[31:0].

This register is present only when EL1 is capable of using AArch32. Otherwise, direct accesses to DACR32_EL2 are undefined.

If EL2 is not implemented but EL3 is implemented, and EL1 is capable of using AArch32, then this register is not res0.

Attributes

DACR32_EL2 is a 64-bit register.

Field descriptions

63 62 61 60 59 58 57 56 55 54 53 52 51 50 49 48 47 46 45 44 43 42 41 40 39 38 37 36 35 34 33 32															
RES0															
D15	D14	D13	D12	D11	D10	D9	D8	D7	D6	D5	D4	D3	D2	D1	D0
31 30	29 28	27 26	25 24	23 22	21 20	19 18	17 16	15 14	13 12	11 10	9 8	7 6	5 4	3 2	1 0

Bits [63:32]

Reserved, res0.

D<n>, bits [2n+1:2n], for n = 15 to 0

Domain n access permission, where n = 0 to 15. Permitted values are:

D<n>	Meaning
0b00	No access. Any access to the domain generates a Domain fault.

0b01	Client. Accesses are checked against the permission bits in the translation tables.
0b11	Manager. Accesses are not checked against the permission bits in the translation tables.

The value 0b10 is reserved.

The reset behavior of this field is:

- On a Warm reset, this field resets to an architecturally unknown value.

Accessing DACR32_EL2

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, DACR32_EL2

op0	op1	CRn	CRm	op2
0b11	0b100	0b0011	0b0000	0b000

```
if !HaveAArch32EL(EL1) then
    UNDEFINED;
elsif PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.NV == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    else
        UNDEFINED;
elsif PSTATE.EL == EL2 then
    X[t, 64] = DACR32_EL2;
elsif PSTATE.EL == EL3 then
    X[t, 64] = DACR32_EL2;
```

MSR DACR32_EL2, <Xt>

op0	op1	CRn	CRm	op2
0b11	0b100	0b0011	0b0000	0b000

```
if !HaveAArch32EL(EL1) then
```

```
    UNDEFINED;
elsif PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.NV == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    else
        UNDEFINED;
elsif PSTATE.EL == EL2 then
    DACR32_EL2 = X[t, 64];
elsif PSTATE.EL == EL3 then
    DACR32_EL2 = X[t, 64];
```

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94