<u>Base</u>	SIMD&FP	<u>SVE</u>	<u>SME</u>	Index by
<u>Instructions</u>	<u>Instructions</u>	<u>Instructions</u>	<u>Instructions</u>	<b>Encoding</b>

Pseu

## EOR3

Bitwise exclusive OR of three vectors

Bitwise exclusive OR the corresponding elements of all three source vectors, and destructively place the results in the corresponding elements of the destination and first source vector. This instruction is unpredicated.

```
31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0 0 0 0 0 0 1 0 0 0 0 1 Zm 0 0 1 1 1 0 Zk Zdn
```

```
EOR3 <Zdn>.D, <Zdn>.D, <Zm>.D, <Zk>.D
if !HaveSVE2() && !HaveSME() then UNDEFINED;
integer m = UInt(Zm);
integer k = UInt(Zk);
integer dn = UInt(Zdn);
```

## **Assembler Symbols**

```
<Zdn> Is the name of the first source and destination scalable vector register, encoded in the "Zdn" field.
<Zm> Is the name of the second source scalable vector register, encoded in the "Zm" field.
<Zk> Is the name of the third source scalable vector register, encoded in the "Zk" field.
```

## Operation

```
CheckSVEEnabled();
constant integer VL = CurrentVL;
bits(VL) operand1 = Z[dn, VL];
bits(VL) operand2 = Z[m, VL];
bits(VL) operand3 = Z[k, VL];

Z[dn, VL] = operand1 EOR operand2 EOR operand3;
```

## **Operational information**

If FEAT\_SVE2 is implemented or FEAT\_SME is implemented, then if PSTATE.DIT is 1:

- The execution time of this instruction is independent of:
  - The values of the data supplied in any of its registers.
  - The values of the NZCV flags.
- The response of this instruction to asynchronous exceptions does not vary based on:
  - The values of the data supplied in any of its registers.
  - The values of the NZCV flags.

This instruction might be immediately preceded in program order by a MOVPRFX instruction. The MOVPRFX instruction must conform to all of the following requirements, otherwise the behavior of the MOVPRFX and this instruction is unpredictable:

- The MOVPRFX instruction must be unpredicated.
- The MOVPRFX instruction must specify the same destination register as this instruction.
- The destination register must not refer to architectural register state referenced by any other source operand register of this instruction.

BaseSIMD&FPSVESMEIndex byInstructionsInstructionsInstructionsInstructions

Internal version only: is a v33.64, AdvSIMD v29.12, pseudocode no\_diffs\_2023\_09\_RC2, sve v2023-06\_rel ; Build timestamp: 2023-09-18T17:56

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.

Sh Pseu