LDCLRB, LDCLRAB, LDCLRALB, LDCLRLB

Atomic bit clear on byte in memory atomically loads an 8-bit byte from memory, performs a bitwise AND with the complement of the value held in a register on it, and stores the result back to memory. The value initially loaded from memory is returned in the destination register.

- If the destination register is not WZR, `LDCLRAB` and `LDCLRALB` load from memory with acquire semantics.
- `LDCLRLB` and `LDCLRALB` store to memory with release semantics.
- `LDCLRB` has neither acquire nor release semantics.

For more information about memory ordering semantics, see *Load-Acquire, Store-Release*.
For information about memory accesses, see *Load/Store addressing modes*.
This instruction is used by the alias STCLRB, STCLRLB.

Integer
(FEAT_LSE)

31 30	29 28 27	26	25 24	23	22	21	20 19 18 17 16	15	14 13 12	11 10	9 8 7 6 5	4 3 2 1 0
0 0	1 1 1	0	0 0	A	R	1	Rs	0	0 0 1	0 0	Rn	Rt
size								opc				

LDCLRAB (A == 1 && R == 0)

```
LDCLRAB <Ws>, <Wt>, [<Xn|SP>]
```

LDCLRALB (A == 1 && R == 1)

```
LDCLRALB <Ws>, <Wt>, [<Xn|SP>]
```

LDCLRB (A == 0 && R == 0)

```
LDCLRB <Ws>, <Wt>, [<Xn|SP>]
```

LDCLRLB (A == 0 && R == 1)

```
LDCLRLB <Ws>, <Wt>, [<Xn|SP>]
```

```
if !IsFeatureImplemented(FEAT_LSE) then UNDEFINED;

integer t = UInt(Rt);
integer n = UInt(Rn);
integer s = UInt(Rs);

boolean acquire = A == '1' && Rt != '11111';
boolean release = R == '1';
boolean tagchecked = n != 31;
```

Assembler Symbols

<Ws>	Is the 32-bit name of the general-purpose register holding the data value to be operated on with the contents of the memory location, encoded in the "Rs" field.
<Wt>	Is the 32-bit name of the general-purpose register to be loaded, encoded in the "Rt" field.
<Xn|SP>	Is the 64-bit name of the general-purpose base register or stack pointer, encoded in the "Rn" field.

Alias Conditions

Alias	Is preferred when
STCLRB, STCLRLB	`A == '0' && Rt == '11111'`

Operation

```
bits(64) address;
bits(8) value;
bits(8) data;

AccessDescriptor accdesc = CreateAccDescAtomicOp(MemAtomicOp_BIC, acqui

value = X[s, 8];
if n == 31 then
    CheckSPAlignment();
    address = SP[];
else
    address = X[n, 64];

bits(8) comparevalue = bits(8) UNKNOWN;    // Irrelevant when not execu
data = MemAtomic(address, comparevalue, value, accdesc);

if t != 31 then
    X[t, 32] = ZeroExtend(data, 32);
```

Operational information

If PSTATE.DIT is 1, the timing of this instruction is insensitive to the value of the data being loaded or stored.

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode no_diffs_2023_09_RC2, sve v2023-06_rel ; Build timestamp: 2023-09-18T17:56