# TRBPIDR7, Peripheral Identification Register 7

The TRBPIDR7 characteristics are:

## **Purpose**

Provides discovery information about the component.

For additional information, see the CoreSight Architecture Specification.

#### **Configuration**

This register is present only when FEAT\_TRBE\_EXT is implemented. Otherwise, direct accesses to TRBPIDR7 are res0.

TRBPIDR7 is in the Core power domain.

#### **Attributes**

TRBPIDR7 is a 32-bit register.

# Field descriptions

31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0

RESO

#### Bits [31:0]

Reserved, res0.

## **Accessing TRBPIDR7**

#### TRBPIDR7 can be accessed through the external debug interface:

Component	Offset	Instance
TRBE	0xFDC	TRBPIDR7

This interface is accessible as follows:

- When DoubleLockStatus() or !IsCorePowered(), accesses to this register generate an error response.
- Otherwise, accesses to this register are **RO**.

AArch32AArch64AArch32AArch64Index byExternalRegistersRegistersInstructionsInstructionsEncodingRegisters

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright  $\hat{A}$  © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.