MDCCSR_EL0, Monitor DCC Status Register

The MDCCSR_EL0 characteristics are:

Purpose

Read-only register containing control status flags for the DCC.

Configuration

AArch64 System register MDCCSR_EL0 bits [30:29] are architecturally mapped to External register [EDSCR[30:29]](#).

AArch64 System register MDCCSR_EL0 bits [30:29] are architecturally mapped to AArch32 System register [DBGDSCRint[30:29]](#).

Attributes

MDCCSR_EL0 is a 64-bit register.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
RES0																															

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
RES0	RXfull	TXfull	RES0										RAZ				RES0	RAZ	RES0					RAZ			RES0				

Bits [63:31]

> Reserved, res0.

RXfull, bit [30]

> DTRRX full. Read-only view of the equivalent bit in the [EDSCR](#).

TXfull, bit [29]

> DTRTX full. Read-only view of the equivalent bit in the [EDSCR](#).

Bits [28:19]

> Reserved, res0.

Bits [18:15]

> Reserved, RAZ.

Bits [14:13]

Reserved, res0.

Bit [12]

Reserved, RAZ.

Bits [11:6]

Reserved, res0.

Bits [5:2]

Reserved, RAZ.

Bits [1:0]

Reserved, res0.

Accessing MDCCSR_EL0

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, MDCCSR_EL0

op0	op1	CRn	CRm	op2
0b10	0b011	0b0000	0b0001	0b000

```
if Halted() &&
ConstrainUnpredictableBool(Unpredictable_IGNORETRAPINDEBUG)
then
    X[t, 64] = MDCCSR_EL0;
elsif PSTATE.EL == EL0 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && MDCR_EL3.TDCC == '1' then
        UNDEFINED;
    elsif Halted() && HaveEL(EL3) && EDSCR.SDD ==
'1' && boolean IMPLEMENTATION_DEFINED "EL3 trap
priority when SDD == '1'" && MDCR_EL3.TDA == '1' then
        UNDEFINED;
    elsif MDSCR_EL1.TDCC == '1' then
        if EL2Enabled() && HCR_EL2.TGE == '1' then
            AArch64.SystemAccessTrap(EL2, 0x18);
        else
            AArch64.SystemAccessTrap(EL1, 0x18);
    elsif EL2Enabled() && MDCR_EL2.TDCC == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
```

```
        elsif EL2Enabled() && (HCR_EL2.TGE == '1' ||
MDCR_EL2.<TDE,TDA> != '00') then
            AArch64.SystemAccessTrap(EL2, 0x18);
        elsif HaveEL(EL3) && MDCR_EL3.TDCC == '1' then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
        elsif HaveEL(EL3) && MDCR_EL3.TDA == '1' then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
        else
            X[t, 64] = MDCCSR_EL0;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && MDCR_EL3.TDCC == '1' then
        UNDEFINED;
    elsif Halted() && HaveEL(EL3) && EDSCR.SDD ==
'1' && boolean IMPLEMENTATION_DEFINED "EL3 trap
priority when SDD == '1'" && MDCR_EL3.TDA == '1' then
        UNDEFINED;
    elsif EL2Enabled() && MDCR_EL2.TDCC == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() && MDCR_EL2.<TDE,TDA> != '00'
then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && MDCR_EL3.TDCC == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    elsif HaveEL(EL3) && MDCR_EL3.TDA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = MDCCSR_EL0;
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && MDCR_EL3.TDCC == '1' then
        UNDEFINED;
    elsif Halted() && HaveEL(EL3) && EDSCR.SDD ==
'1' && boolean IMPLEMENTATION_DEFINED "EL3 trap
priority when SDD == '1'" && MDCR_EL3.TDA == '1' then
        UNDEFINED;
    elsif HaveEL(EL3) && MDCR_EL3.TDCC == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    elsif HaveEL(EL3) && MDCR_EL3.TDA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
```

```
        else
            X[t, 64] = MDCCSR_EL0;
    elsif PSTATE.EL == EL3 then
        X[t, 64] = MDCCSR_EL0;
```

28/03/2023 16:01; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94