GPTBR_EL3, Granule Protection Table Base Register

The GPTBR_EL3 characteristics are:

Purpose

The control register for Granule Protection Table base address.

Configuration

This register is present only when FEAT_RME is implemented. Otherwise, direct accesses to GPTBR_EL3 are undefined.

Attributes

GPTBR_EL3 is a 64-bit register.

Field descriptions

63 62 61 60 59 58 57 56 55 54 53 52 51 50 49 48 47 46 45 44 43 42 41 40	39 38 37 36 35 34 33 32
RES0	BADDR
BADDR	
31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0	

Bits [63:40]

Reserved, res0.

BADDR, bits [39:0]

Base address for the level 0 GPT.

This field represents bits [51:12] of the level 0 GPT base address.

The level 0 GPT is aligned in memory to the greater of:

- The size of the level 0 GPT in bytes.
- 4KB.

Bits [x:0] of the base address are treated as zero, where:

- x = Max(pps - l0gptsz + 2, 11)
- pps is derived from GPCCR_EL3.PPS as follows:

GPCCR_EL3.PPS	pps
0b000	32
0b001	36
0b010	40
0b011	42
0b100	44
0b101	48
0b110	52

- l0gptsz is derived from GPCCR_EL3.L0GPTSZ as follows:

GPCCR_EL3.L0GPTSZ	l0gptsz
0b0000	30
0b0100	34
0b0110	36
0b1001	39

If x is greater than 11, then BADDR[x - 12:0] are res0.

The reset behavior of this field is:

- On a Warm reset, this field resets to an architecturally unknown value.

Accessing GPTBR_EL3

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, GPTBR_EL3

op0	op1	CRn	CRm	op2
0b11	0b110	0b0010	0b0001	0b100

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    UNDEFINED;
elsif PSTATE.EL == EL2 then
    UNDEFINED;
elsif PSTATE.EL == EL3 then
    X[t, 64] = GPTBR_EL3;
```

MSR GPTBR_EL3, <Xt>

op0	op1	CRn	CRm	op2
0b11	0b110	0b0010	0b0001	0b100

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    UNDEFINED;
elsif PSTATE.EL == EL2 then
    UNDEFINED;
elsif PSTATE.EL == EL3 then
    GPTBR_EL3 = X[t, 64];
```

28/03/2023 16:01; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94