AMAIR2_EL2, Extended Auxiliary Memory Attribute Indirection Register (EL2)

The AMAIR2_EL2 characteristics are:

Purpose

Provides implementation defined memory attributes for the memory regions specified by MAIR2_EL2.

Configuration

This register is present only when FEAT_AIE is implemented. Otherwise, direct accesses to AMAIR2_EL2 are undefined.

Attributes

AMAIR2_EL2 is a 64-bit register.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
IMPLEMENTATION DEFINED																															
IMPLEMENTATION DEFINED																															
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0

IMPLEMENTATION DEFINED, bits [63:0]

implementation defined.

Accessing AMAIR2_EL2

When FEAT_VHE is implemented, and HCR_EL2.E2H is 1, without explicit synchronization, accesses from EL2 using the register name AMAIR2_EL2 or AMAIR2_EL1 are not guaranteed to be ordered with respect to accesses using the other register name.

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, AMAIR2_EL2

op0	op1	CRn	CRm	op2
0b11	0b100	0b1010	0b0011	0b001

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.NV == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    else
        UNDEFINED;
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.AIEn == '0' then
        UNDEFINED;
    elsif HaveEL(EL3) && SCR_EL3.AIEn == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = AMAIR2_EL2;
elsif PSTATE.EL == EL3 then
    X[t, 64] = AMAIR2_EL2;
```

MSR AMAIR2_EL2, <Xt>

op0	op1	CRn	CRm	op2
0b11	0b100	0b1010	0b0011	0b001

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.NV == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    else
        UNDEFINED;
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.AIEn == '0' then
        UNDEFINED;
    elsif HaveEL(EL3) && SCR_EL3.AIEn == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
```

```
    else
        AMAIR2_EL2 = X[t, 64];
elsif PSTATE.EL == EL3 then
    AMAIR2_EL2 = X[t, 64];
```

MRS <Xt>, AMAIR2_EL1

op0	op1	CRn	CRm	op2
0b11	0b000	0b1010	0b0011	0b001

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.AIEn == '0' then
        UNDEFINED;
    elsif EL2Enabled() && HCR_EL2.TRVM == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
SCR_EL3.FGTEn == '1') && HFGRTR_EL2.nAMAIR2_EL1 ==
'0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && SCR_EL3.AIEn == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    elsif EL2Enabled() && HCR_EL2.<NV2,NV1,NV> ==
'111' then
        X[t, 64] = NVMem[0x288];
    else
        X[t, 64] = AMAIR2_EL1;
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.AIEn == '0' then
        UNDEFINED;
    elsif HaveEL(EL3) && SCR_EL3.AIEn == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    elsif HCR_EL2.E2H == '1' then
        X[t, 64] = AMAIR2_EL2;
    else
        X[t, 64] = AMAIR2_EL1;
elsif PSTATE.EL == EL3 then
    X[t, 64] = AMAIR2_EL1;
```

MSR AMAIR2_EL1, <Xt>

op0	op1	CRn	CRm	op2
0b11	0b000	0b1010	0b0011	0b001

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.AIEn == '0' then
        UNDEFINED;
    elsif EL2Enabled() && HCR_EL2.TVM == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
SCR_EL3.FGTEn == '1') && HFGWTR_EL2.nAMAIR2_EL1 ==
'0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && SCR_EL3.AIEn == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    elsif EL2Enabled() && HCR_EL2.<NV2,NV1,NV> ==
'111' then
        NVMem[0x288] = X[t, 64];
    else
        AMAIR2_EL1 = X[t, 64];
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.AIEn == '0' then
        UNDEFINED;
    elsif HaveEL(EL3) && SCR_EL3.AIEn == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    elsif HCR_EL2.E2H == '1' then
        AMAIR2_EL2 = X[t, 64];
    else
        AMAIR2_EL1 = X[t, 64];
elsif PSTATE.EL == EL3 then
    AMAIR2_EL1 = X[t, 64];
```