SCVTF

Signed integer convert to floating-point (predicated)

Convert to floating-point from the signed integer in each active element of the source vector, and place the results in the corresponding elements of the destination vector. Inactive elements in the destination vector register remain unmodified.

If the input and result types have a different size the smaller type is held unpacked in the least significant bits of elements of the larger size. When the input is the smaller type the upper bits of each source element are ignored. When the result is the smaller type the results are zero-extended to fill each destination element.

It has encodings from 7 classes: 16-bit to half-precision , 32-bit to half-precision , 32-bit to single-precision , 32-bit to double-precision , 64-bit to half-precision , 64-bit to single-precision and 64-bit to double-precision

16-bit to half-precision



SCVTF <Zd>.H, <Pg>/M, <Zn>.H

```
if !HaveSVE() && !HaveSME() then UNDEFINED;
constant integer esize = 16;
integer g = UInt(Pg);
integer n = UInt(Zn);
integer d = UInt(Zd);
constant integer s_esize = 16;
constant integer d_esize = 16;
boolean unsigned = FALSE;
FPRounding rounding = FPRoundingMode(FPCR[]);
```

32-bit to half-precision



SCVTF <Zd>.H, <Pg>/M, <Zn>.S

```
if !HaveSVE() && !HaveSME() then UNDEFINED;
constant integer esize = 32;
integer g = UInt(Pg);
integer n = UInt(Zn);
integer d = UInt(Zd);
constant integer s_esize = 32;
constant integer d_esize = 16;
boolean unsigned = FALSE;
FPRounding rounding = FPRoundingMode(FPCR[]);
```

32-bit to single-precision



SCVTF <Zd>.S, <Pg>/M, <Zn>.S

```
if !HaveSVE() && !HaveSME() then UNDEFINED;
constant integer esize = 32;
integer g = UInt(Pg);
integer n = UInt(Zn);
integer d = UInt(Zd);
constant integer s_esize = 32;
constant integer d_esize = 32;
boolean unsigned = FALSE;
FPRounding rounding = FPRoundingMode(FPCR[]);
```

32-bit to double-precision



SCVTF <Zd>.D, <Pg>/M, <Zn>.S

```
if !HaveSVE() && !HaveSME() then UNDEFINED;
constant integer esize = 64;
integer g = UInt(Pg);
integer n = UInt(Zn);
integer d = UInt(Zd);
constant integer s_esize = 32;
constant integer d_esize = 64;
boolean unsigned = FALSE;
FPRounding rounding = FPRoundingMode(FPCR[]);
```

64-bit to half-precision



SCVTF <Zd>.H, <Pg>/M, <Zn>.D

```
if !HaveSVE() && !HaveSME() then UNDEFINED;
constant integer esize = 64;
integer g = UInt(Pg);
integer n = UInt(Zn);
integer d = UInt(Zd);
constant integer s_esize = 64;
constant integer d_esize = 16;
boolean unsigned = FALSE;
FPRounding rounding = FPRoundingMode(FPCR[]);
```

64-bit to single-precision



SCVTF <Zd>.S, <Pg>/M, <Zn>.D

```
if !HaveSVE() && !HaveSME() then UNDEFINED;
constant integer esize = 64;
integer g = UInt(Pg);
integer n = UInt(Zn);
integer d = UInt(Zd);
constant integer s_esize = 64;
constant integer d_esize = 32;
boolean unsigned = FALSE;
FPRounding rounding = FPRoundingMode(FPCR[]);
```

64-bit to double-precision



SCVTF <Zd>.D, <Pg>/M, <Zn>.D

```
if !HaveSVE() && !HaveSME() then UNDEFINED;
constant integer esize = 64;
integer g = UInt(Pg);
integer n = UInt(Zn);
integer d = UInt(Zd);
constant integer s_esize = 64;
constant integer d_esize = 64;
boolean unsigned = FALSE;
FPRounding rounding = FPRoundingMode(FPCR[]);
```

Assembler Symbols

<Zd>	Is the name of the destination scalable vector register, encoded in the "Zd" field.
<Pg>	Is the name of the governing scalable predicate register P0-P7, encoded in the "Pg" field.

<Zn> Is the name of the source scalable vector register, encoded in the "Zn" field.

Operation

```
CheckSVEEnabled();
constant integer VL = CurrentVL;
constant integer PL = VL DIV 8;
constant integer elements = VL DIV esize;
bits(PL) mask = P[g, PL];
bits(VL) operand = if AnyActiveElement(mask, esize) then Z[n, VL] else
bits(VL) result = Z[d, VL];

for e = 0 to elements-1
    if ActivePredicateElement(mask, e, esize) then
        bits(esize) element = Elem[operand, e, esize];
        bits(d_esize) fpval = FixedToFP(element<s_esize-1:0>, 0, unsign
        Elem[result, e, esize] = ZeroExtend(fpval, esize);

Z[d, VL] = result;
```

Operational information

This instruction might be immediately preceded in program order by a MOVPRFX instruction. The MOVPRFX instruction must conform to all of the following requirements, otherwise the behavior of the MOVPRFX and this instruction is unpredictable:

- The MOVPRFX instruction must be unpredicated, or be predicated using the same governing predicate register and source element size as this instruction.
- The MOVPRFX instruction must specify the same destination register as this instruction.
- The destination register must not refer to architectural register state referenced by any other source operand register of this instruction.

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode no_diffs_2023_09_RC2, sve v2023-06_rel ; Build timestamp: 2023-09-18T17:56