

BSL

Bitwise select

Selects bits from the first source vector where the corresponding bit in the third source vector is '1', and from the second source vector where the corresponding bit in the third source vector is '0'. The result is placed destructively in the destination and first source vector. This instruction is unpredicated.

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	0	0	0	0	1	0	0	0	0	1	Zm			0			0	1	1	1	1	Zk			Zdn						

BSL [<Zdn>.D](#), [<Zdn>.D](#), [<Zm>.D](#), [<Zk>.D](#)

```
if !HaveSVE2() && !HaveSME() then UNDEFINED;
integer m = UInt(Zm);
integer k = UInt(Zk);
integer dn = UInt(Zdn);
```

Assembler Symbols

- [<Zdn>](#) Is the name of the first source and destination scalable vector register, encoded in the "Zdn" field.
- [<Zm>](#) Is the name of the second source scalable vector register, encoded in the "Zm" field.
- [<Zk>](#) Is the name of the third source scalable vector register, encoded in the "Zk" field.

Operation

```
CheckSVEEnabled();
constant integer VL = CurrentVL;
bits(VL) operand1 = Z[dn, VL];
bits(VL) operand2 = Z[m, VL];
bits(VL) operand3 = Z[k, VL];

Z[dn, VL] = (operand1 AND operand3) OR (operand2 AND NOT(operand3));
```

Operational information

If FEAT_SVE2 is implemented or FEAT_SME is implemented, then if PSTATE.DIT is 1:

- The execution time of this instruction is independent of:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.

- The response of this instruction to asynchronous exceptions does not vary based on:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.

This instruction might be immediately preceded in program order by a MOVPRFX instruction. The MOVPRFX instruction must conform to all of the following requirements, otherwise the behavior of the MOVPRFX and this instruction is unpredictable:

- The MOVPRFX instruction must be unpredicated.
- The MOVPRFX instruction must specify the same destination register as this instruction.
- The destination register must not refer to architectural register state referenced by any other source operand register of this instruction.

[Base
Instructions](#)

[SIMD&FP
Instructions](#)

[SVE
Instructions](#)

[SME
Instructions](#)

[Index by
Encoding](#)

[Sh
Pseu](#)

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode no_diffs_2023_09_RC2, sve v2023-06_rel ; Build timestamp: 2023-09-18T17:56

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.