AMCNTENSET0_EL0, Activity Monitors Count Enable Set Register 0

The AMCNTENSET0_EL0 characteristics are:

Purpose

Enable control bits for the architected activity monitors event counters, AMEVCNTR0<n>_EL0.

Configuration

AArch64 System register AMCNTENSET0_EL0 bits [31:0] are architecturally mapped to AArch32 System register AMCNTENSET0[31:0].

AArch64 System register AMCNTENSET0_EL0 bits [31:0] are architecturally mapped to External register AMCNTENSET0[31:0].

This register is present only when FEAT_AMUv1 is implemented. Otherwise, direct accesses to AMCNTENSET0_EL0 are undefined.

Attributes

AMCNTENSET0_EL0 is a 64-bit register.

Field descriptions



Bits [63:16]

Reserved, res0.

Bits [15:4]

Reserved, RAZ/WI.

This field is reserved for additional architected activity monitor event counters, which Arm might define in a future version of the Activity Monitors architecture.

P<n>, bit [n], for n = 3 to 0

Activity monitor event counter enable bit for AMEVCNTR0<n>_EL0.

Note

AMCGCR_EL0.CG0NC identifies the number of architected activity monitor event counters. In an implementation that includes FEAT_AMUv1, the number of architected activity monitor event counters is 4.

Possible values of each bit are:

P<n>	Meaning
0b0	When read, means that AMEVCNTR0<n>_EL0 is disabled. When written, has no effect.
0b1	When read, means that AMEVCNTR0<n>_EL0 is enabled. When written, enables AMEVCNTR0<n>_EL0.

The reset behavior of this field is:

- On an AMU reset, this field resets to 0.

Accessing AMCNTENSET0_EL0

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, AMCNTENSET0_EL0

op0	op1	CRn	CRm	op2
0b11	0b011	0b1101	0b0010	0b101

```
if PSTATE.EL == EL0 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && CPTR_EL3.TAM == '1' then
        UNDEFINED;
    elsif AMUSERENR_EL0.EN == '0' then
        if EL2Enabled() && HCR_EL2.TGE == '1' then
            AArch64.SystemAccessTrap(EL2, 0x18);
```

```
        else
            AArch64.SystemAccessTrap(EL1, 0x18);
    elsif EL2Enabled() && CPTR_EL2.TAM == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() && HCR_EL2.<E2H,TGE> != '11'
&& IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3)
|| SCR_EL3.FGTEn == '1') && HAFGRTR_EL2.AMCNTEN0 ==
'1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && CPTR_EL3.TAM == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = AMCNTENSET0_EL0;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && CPTR_EL3.TAM == '1' then
        UNDEFINED;
    elsif EL2Enabled() && CPTR_EL2.TAM == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
SCR_EL3.FGTEn == '1') && HAFGRTR_EL2.AMCNTEN0 == '1'
then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && CPTR_EL3.TAM == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = AMCNTENSET0_EL0;
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && CPTR_EL3.TAM == '1' then
        UNDEFINED;
    elsif HaveEL(EL3) && CPTR_EL3.TAM == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = AMCNTENSET0_EL0;
elsif PSTATE.EL == EL3 then
    X[t, 64] = AMCNTENSET0_EL0;
```

MSR AMCNTENSET0_EL0, <Xt>

op0	op1	CRn	CRm	op2
0b11	0b011	0b1101	0b0010	0b101

```
if IsHighestEL(PSTATE.EL) then
    AMCNTENSET0_EL0 = X[t, 64];
else
    UNDEFINED;
```

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94