SVE	SME	Index by
Instructions	Instructions	Encoding

Pseu

## FRINTN (scalar)

<u>Base</u> Instructions

Floating-point Round to Integral, to nearest with ties to even (scalar). This instruction rounds a floating-point value in the SIMD&FP source register to an integral floating-point value of the same size using the Round to Nearest rounding mode, and writes the result to the SIMD&FP destination register.

SIMD&FP

Instructions

A zero input gives a zero result with the same sign, an infinite input gives an infinite result with the same sign, and a NaN is propagated as for normal arithmetic.

A floating-point exception can be generated by this instruction. Depending on the settings in *FPCR*, the exception results in either a flag being set in *FPSR*, or a synchronous exception being generated. For more information, see *Floating-point exception traps*.

Depending on the settings in the *CPACR\_EL1*, *CPTR\_EL2*, and *CPTR\_EL3* registers, and the current Security state and Exception level, an attempt to execute the instruction might be trapped.

```
31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0

0 0 0 1 1 1 1 0 ftype 1 0 0 1 0 0 0 1 0 0 0 Rn Rd

rmode
```

```
Half-precision (ftype == 11) (FEAT_FP16)
```

```
FRINTN <Hd>, <Hn>
```

Single-precision (ftype == 00)

```
FRINTN <Sd>, <Sn>
```

## Double-precision (ftype == 01)

```
FRINTN <Dd>, <Dn>
if ftype == '10' || (ftype == '11' && !IsFeatureImplemented(FEAT_FP16))
integer d = UInt(Rd);
integer n = UInt(Rn);

constant integer esize = 8 << UInt(ftype EOR '10');
FPRounding rounding;
rounding = FPDecodeRounding('00');</pre>
```

## **Assembler Symbols**

< Dd >

Is the 64-bit name of the SIMD&FP destination register, encoded in the "Rd" field.

<dn></dn>	Is the 64-bit name of the SIMD&FP source register, encoded in the "Rn" field.
<hd></hd>	Is the 16-bit name of the SIMD&FP destination register, encoded in the "Rd" field.
<hn></hn>	Is the 16-bit name of the SIMD&FP source register, encoded in the "Rn" field.
<sd></sd>	Is the 32-bit name of the SIMD&FP destination register, encoded in the "Rd" field.
<sn></sn>	Is the 32-bit name of the SIMD&FP source register, encoded in the "Rn" field.

## **Operation**

```
CheckFPEnabled64();

FPCRType fpcr = FPCR[];
boolean merge = IsMerging(fpcr);
bits(128) result = if merge then V[d, 128] else Zeros(128);
bits(esize) operand = V[n, esize];

Elem[result, 0, esize] = FPRoundInt(operand, fpcr, rounding, FALSE);
V[d, 128] = result;
```

Sh

Pseu

<u>Base</u> <u>SIMD&FP</u> <u>SVE</u> <u>SME</u> <u>Index by</u> Instructions Instructions Instructions Encoding

Internal version only: is a v33.64, AdvSIMD v29.12, pseudocode no\_diffs\_2023\_09\_RC2, sve v2023-06\_rel ; Build timestamp: 2023-09-18T17:56

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.