AArch64 Instructions Index by Encoding External Registers

SPMSELR_ELO, System Performance Monitors Select Register

The SPMSELR EL0 characteristics are:

Purpose

Selects the System PMU and event counter registers to access.

Configuration

This register is present only when FEAT_SPMU is implemented. Otherwise, direct accesses to SPMSELR EL0 are undefined.

Attributes

SPMSELR EL0 is a 64-bit register.

Field descriptions

63 62 61 60 59 58 57 56 55 54 53 52 51 50 49 48 47 46 45 44 43 42 41 40 39 38 37 36 35 34 33 32

RESO

RESO

SYSPMUSEL RESOBANK

31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0

Bits [63:10]

Reserved, res0.

SYSPMUSEL, bits [9:4]

System PMU Select. Selects a System PMU <s> to access.

Values 0x20 to 0x3F are reserved.

The reset behavior of this field is:

• On a Warm reset, this field resets to an architecturally unknown value.

Bits [3:2]

Reserved, res0.

BANK, bits [1:0]

System PMU bank access control. Selects a bank of 16 System PMU event counters and related controls to access.

BANK	Meaning
0b00	Select event counters 0 to 15.
0b01	Select event counters 16 to 31.
0b10	Select event counters 32 to 47.
0b11	Select event counters 48 to 63.

The reset behavior of this field is:

• On a Warm reset, this field resets to an architecturally unknown value.

Accessing SPMSELR_EL0

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, SPMSELR EL0

op0	op1	CRn	CRm	op2
0b10	0b011	0b1001	0b1100	0b101

```
if PSTATE.EL == ELO then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && MDCR_EL3.EnPM2 == '0' then
        UNDEFINED;
    elsif EL2Enabled() && HCR EL2.<E2H, TGE> != '11'
&& IsFeatureImplemented(FEAT FGT2) && HaveEL(EL3) &&
SCR EL3.FGTEn2 == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() && HCR_EL2.<E2H,TGE> != '11'
&& IsFeatureImplemented(FEAT_FGT2) &&
HDFGRTR2_EL2.nSPMSELR_EL0 == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && MDCR_EL3.EnPM2 == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = SPMSELR\_ELO;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && MDCR_EL3.EnPM2 == '0' then
```

```
UNDEFINED;
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT2) && HaveEL(EL3) &&
SCR_EL3.FGTEn2 == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT2) &&
HDFGRTR2_EL2.nSPMSELR_EL0 == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && MDCR EL3.EnPM2 == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED:
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = SPMSELR\_ELO;
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION DEFINED "EL3 trap priority
when SDD == '1'" && MDCR EL3.EnPM2 == '0' then
        UNDEFINED;
    elsif HaveEL(EL3) && MDCR_EL3.EnPM2 == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = SPMSELR ELO;
elsif PSTATE.EL == EL3 then
    X[t, 64] = SPMSELR ELO;
```

MSR SPMSELR_EL0, <Xt>

op0	op1	CRn	CRm	op2
0b10	0b011	0b1001	0b1100	0b101

```
if PSTATE.EL == ELO then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && MDCR_EL3.EnPM2 == '0' then
        UNDEFINED;
    elsif EL2Enabled() && HCR_EL2.<E2H,TGE> != '11'
&& IsFeatureImplemented(FEAT_FGT2) && HaveEL(EL3) &&
SCR_EL3.FGTEn2 == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() && HCR_EL2.<E2H,TGE> != '11'
&& IsFeatureImplemented(FEAT_FGT2) &&
HDFGWTR2_EL2.nSPMSELR_EL0 == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && MDCR_EL3.EnPM2 == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
```

```
AArch64.SystemAccessTrap(EL3, 0x18);
    else
        SPMSELR ELO = X[t, 64];
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION DEFINED "EL3 trap priority
when SDD == '1'" && MDCR_EL3.EnPM2 == '0' then
        UNDEFINED;
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT FGT2) && HaveEL(EL3) &&
SCR EL3.FGTEn2 == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT FGT2) &&
HDFGWTR2_EL2.nSPMSELR_EL0 == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && MDCR_EL3.EnPM2 == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        SPMSELR\_EL0 = X[t, 64];
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && MDCR_EL3.EnPM2 == '0' then
        UNDEFINED;
    elsif HaveEL(EL3) && MDCR EL3.EnPM2 == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        SPMSELR ELO = X[t, 64];
elsif PSTATE.EL == EL3 then
    SPMSELR ELO = X[t, 64];
```

AArch32 Registers AArch64 Registers AArch32 Instructions AArch64
Instructions

Index by Encoding

External Registers

28/03/2023 16:01; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.