ERR<n>MISC1, Error Record <n> Miscellaneous Register 1, n = 0 - 65534

The ERR<n>MISC1 characteristics are:

Purpose

implementation defined error syndrome register. The miscellaneous syndrome registers might contain:

- Information to locate where the error was detected.
- If the error was detected within a FRU, the identity of the FRU.
- A Corrected error counter or counters.
- Other state information not present in the corresponding status and address registers.

Configuration

This register is present only when error record <n> is implemented. Otherwise, direct accesses to ERR<n>MISC1 are res0.

ERR<q>FR describes the features implemented by the node that owns error record <n>. <q> is the index of the first error record owned by the same node as error record <n>. If the node owns a single record then q = n.

For implementation defined fields in ERR<n>MISC1, writing zero returns the error record to an initial quiescent state.

In particular, if any implementation defined syndrome fields might generate a Fault Handling or Error Recovery Interrupt request, writing zero is sufficient to deactivate the Interrupt request.

Fields that are read-only, nonzero, and ignore writes are compliant with this requirement.

Note

Arm recommends that any implementation defined syndrome field that can generate a Fault Handling, Error Recovery, Critical, or implementation defined, interrupt request is disabled at Cold reset and is enabled by software writing an implementation defined nonzero value to an implementation defined field in ERR<q>CTLR.

Attributes

ERR<n>MISC1 is a 64-bit register.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
IMPLEMENTATION DEFINED																															
IMPLEMENTATION DEFINED																															
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0

IMPLEMENTATION DEFINED, bits [63:0]

implementation defined syndrome.

Accessing ERR<n>MISC1

Reads from ERR<n>MISC1 return an implementation defined value and writes have implementation defined behavior.

If the Common Fault Injection Mechanism is implemented by the node that owns this error record, and ERR<q>PFGF.MV is 1, then some parts of this register are read/write when ERR<n>STATUS.MV is 0. See ERR<n>PFGF.MV for more information.

For other parts of this register, or if the Common Fault Injection Mechanism is not implemented, then Arm recommends that:

- Miscellaneous syndrome for multiple errors, such as a corrected error counter, is read/write.
- When ERR<n>STATUS.MV is 1, the miscellaneous syndrome specific to the most recently recorded error ignores writes.

Note

These recommendations allow a counter to be reset in the presence of a persistent error, while preventing specific information, such as that identifying a FRU, from being lost if an error is detected while the previous error is being logged.

ERR<n>MISC1 can be accessed through the memory-mapped interfaces:

Component	Offset	Instance
RAS	`0x028` + (64 * n)	ERR<n>MISC1

Accesses on this interface are **RW**.

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94