

TRCVISSCTLR, ViewInst Start/Stop Control Register

The TRCVISSCTLR characteristics are:

Purpose

Use this to select, or read, the Single Address Comparators for the ViewInst start/stop function.

Configuration

AArch64 System register TRCVISSCTLR bits [31:0] are architecturally mapped to External register [TRCVISSCTLR\[31:0\]](#).

This register is present only when FEAT_ETE is implemented, FEAT_TRC_SR is implemented and $\text{UInt}(\text{TRCIDR4.NUMACPAIRS}) > 0$. Otherwise, direct accesses to TRCVISSCTLR are undefined.

Attributes

TRCVISSCTLR is a 64-bit register.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53
STOP[15]	STOP[14]	STOP[13]	STOP[12]	STOP[11]	STOP[10]	STOP[9]	STOP[8]	STOP[7]	STOP[6]	STOP[5]
31	30	29	28	27	26	25	24	23	22	21

Bits [63:32]

Reserved, res0.

STOP[<m>], bit [m+16], for m = 15 to 0

Selects whether Single Address Comparator <m> is used with the ViewInst start/stop function, for the purpose of stopping trace.

STOP[<m>]	Meaning
0b0	The Single Address Comparator <m>, is not selected as a stop resource.

0b1	The Single Address Comparator <m>, is selected as a stop resource.
-----	--

This bit is res0 if $m \geq 2 \text{ } \tilde{\text{A}} \text{---}$ [TRCIDR4](#).NUMACPAIRS.

The reset behavior of this field is:

- On a Trace unit reset, this field resets to an architecturally unknown value.

START[<m>], bit [m], for m = 15 to 0

Selects whether Single Address Comparator <m> is used with the ViewInst start/stop function, for the purpose of starting trace.

START[<m>]	Meaning
0b0	The Single Address Comparator <m>, is not selected as a start resource.
0b1	The Single Address Comparator <m>, is selected as a start resource.

This bit is res0 if $m \geq 2 \text{ } \tilde{\text{A}} \text{---}$ [TRCIDR4](#).NUMACPAIRS.

The reset behavior of this field is:

- On a Trace unit reset, this field resets to an architecturally unknown value.

Accessing TRCVISSCTLR

Must be programmed if [TRCIDR4](#).NUMACPAIRS > 0b0000.

For any 2 comparators selected for the ViewInst start/stop function, the comparator containing the lower address must be a lower numbered comparator.

Writes are constrained unpredictable if the trace unit is not in the Idle state.

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, TRCVISSCTLR

op0	op1	CRn	CRm	op2
0b10	0b001	0b0000	0b0010	0b010

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
    && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
    when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
    elsif CPACR_EL1.TTA == '1' then
        AArch64.SystemAccessTrap(EL1, 0x18);
    elsif EL2Enabled() && CPTR_EL2.TTA == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
    IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
    SCR_EL3.FGTEn == '1') && HDFGRTR_EL2.TRC == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            X[t, 64] = TRCVISSCTLR;
    elsif PSTATE.EL == EL2 then
        if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
        && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
        when SDD == '1'" && CPTR_EL3.TTA == '1' then
            UNDEFINED;
        elsif CPTR_EL2.TTA == '1' then
            AArch64.SystemAccessTrap(EL2, 0x18);
        elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
            else
                X[t, 64] = TRCVISSCTLR;
    elsif PSTATE.EL == EL3 then
        if CPTR_EL3.TTA == '1' then
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            X[t, 64] = TRCVISSCTLR;
```

MSR TRCVISSCTLR, <Xt>

op0	op1	CRn	CRm	op2
-----	-----	-----	-----	-----

0b10	0b001	0b0000	0b0010	0b010
------	-------	--------	--------	-------

```

if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
    && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
    elsif CPACR_EL1.TTA == '1' then
        AArch64.SystemAccessTrap(EL1, 0x18);
    elsif EL2Enabled() && CPTR_EL2.TTA == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
SCR_EL3.FGTEn == '1') && HDFGWTR_EL2.TRC == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            TRCVISSCTLR = X[t, 64];
    elsif PSTATE.EL == EL2 then
        if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
        && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && CPTR_EL3.TTA == '1' then
            UNDEFINED;
        elsif CPTR_EL2.TTA == '1' then
            AArch64.SystemAccessTrap(EL2, 0x18);
        elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
            else
                TRCVISSCTLR = X[t, 64];
    elsif PSTATE.EL == EL3 then
        if CPTR_EL3.TTA == '1' then
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            TRCVISSCTLR = X[t, 64];

```

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.