TRCSEQEVR<n>, Sequencer State Transition Control Register <n>, n = 0 - 2

The TRCSEQEVR<n> characteristics are:

Purpose

Moves the Sequencer state:

- Backwards, from state n+1 to state n when a programmed resource event occurs.
- Forwards, from state n to state n+1 when a programmed resource event occurs.

Configuration

AArch64 System register TRCSEQEVR<n> bits [31:0] are architecturally mapped to External register TRCSEQEVR<n>[31:0].

This register is present only when FEAT_ETE is implemented, FEAT_TRC_SR is implemented and TRCIDR5.NUMSEQSTATE != 0b000. Otherwise, direct accesses to TRCSEQEVR<n> are undefined.

Attributes

TRCSEQEVR<n> is a 64-bit register.

Field descriptions



Bits [63:16]

Reserved, res0.

B_TYPE, bit [15]

Chooses the type of Resource Selector.

Backward field. Defines whether the backward resource event is a single Resource Selector or a Resource Selector pair. When the resource event occurs then the Sequencer state moves from state n+1 to state n. For example, if TRCSEQEVR2.B.SEL == `0x14` then

when event `0x14` occurs, the Sequencer moves from state 3 to state 2.

B_TYPE	Meaning
`0b0`	A single Resource Selector. TRCSEQEVR<n>.B.SEL[4:0] selects the single Resource Selector, from 0-31, used to activate the resource event.
`0b1`	A Boolean-combined pair of Resource Selectors. TRCSEQEVR<n>.B.SEL[3:0] selects the Resource Selector pair, from 0-15, that has a Boolean function that is applied to it whose output is used to activate the resource event. TRCSEQEVR<n>.B.SEL[4] is res0.

The reset behavior of this field is:

- On a Trace unit reset, this field resets to an architecturally unknown value.

Bits [14:13]

Reserved, res0.

B_SEL, bits [12:8]

Defines the selected Resource Selector or pair of Resource Selectors. TRCSEQEVR<n>.B.TYPE controls whether TRCSEQEVR<n>.B.SEL is the index of a single Resource Selector, or the index of a pair of Resource Selectors.

Backward field. Selects the single Resource Selector or Resource Selector pair.

If an unimplemented Resource Selector is selected using this field, the behavior of the resource event is unpredictable, and the resource event might fire or might not fire when the resources are not in the Paused state.

Selecting Resource Selector pair 0 using this field is unpredictable, and the resource event might fire or might not fire when the resources are not in the Paused state.

The reset behavior of this field is:

- On a Trace unit reset, this field resets to an architecturally unknown value.

F_TYPE, bit [7]

Chooses the type of Resource Selector.

Backward field. Defines whether the forward resource event is a single Resource Selector or a Resource Selector pair. When the resource event occurs then the Sequencer state moves from state n to state n+1. For example, if TRCSEQEVR1.F.SEL == `0x12` then when event `0x12` occurs, the Sequencer moves from state 1 to state 2.

F_TYPE	Meaning
`0b0`	A single Resource Selector. TRCSEQEVR<n>.F.SEL[4:0] selects the single Resource Selector, from 0-31, used to activate the resource event.
`0b1`	A Boolean-combined pair of Resource Selectors. TRCSEQEVR<n>.F.SEL[3:0] selects the Resource Selector pair, from 0-15, that has a Boolean function that is applied to it whose output is used to activate the resource event. TRCSEQEVR<n>.F.SEL[4] is res0.

The reset behavior of this field is:

- On a Trace unit reset, this field resets to an architecturally unknown value.

Bits [6:5]

Reserved, res0.

F_SEL, bits [4:0]

Defines the selected Resource Selector or pair of Resource Selectors. TRCSEQEVR<n>.F.TYPE controls whether TRCSEQEVR<n>.F.SEL is the index of a single Resource Selector, or the index of a pair of Resource Selectors.

Forward field. Selects the single Resource Selector or Resource Selector pair.

If an unimplemented Resource Selector is selected using this field, the behavior of the resource event is unpredictable, and the resource event might fire or might not fire when the resources are not in the Paused state.

Selecting Resource Selector pair 0 using this field is unpredictable, and the resource event might fire or might not fire when the resources are not in the Paused state.

The reset behavior of this field is:

- On a Trace unit reset, this field resets to an architecturally unknown value.

Accessing TRCSEQEVR<n>

Must be programmed if TRCRSCTLR<a>.GROUP == `0b0010` and TRCRSCTLR<a>.SEQUENCER != `0b0000`.

Writes are constrained unpredictable if the trace unit is not in the Idle state.

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, TRCSEQEVR<m> ; Where m = 0-2

op0	op1	CRn	CRm	op2
0b10	0b001	0b0000	0b00:m[1:0]	0b100

```
integer m = UInt(CRm<1:0>);

if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
    elsif CPACR_EL1.TTA == '1' then
        AArch64.SystemAccessTrap(EL1, 0x18);
    elsif EL2Enabled() && CPTR_EL2.TTA == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
SCR_EL3.FGTEn == '1') && HDFGRTR_EL2.TRC == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
```

```
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = TRCSEQEVR[m];
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
    elsif CPTR_EL2.TTA == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = TRCSEQEVR[m];
elsif PSTATE.EL == EL3 then
    if CPTR_EL3.TTA == '1' then
        AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = TRCSEQEVR[m];
```

MSR TRCSEQEVR<m>, <Xt> ; Where m = 0-2

op0	op1	CRn	CRm	op2
0b10	0b001	0b0000	0b00:m[1:0]	0b100

```
integer m = UInt(CRm<1:0>);

if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
    elsif CPACR_EL1.TTA == '1' then
        AArch64.SystemAccessTrap(EL1, 0x18);
    elsif EL2Enabled() && CPTR_EL2.TTA == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
SCR_EL3.FGTEn == '1') && HDFGWTR_EL2.TRC == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        TRCSEQEVR[m] = X[t, 64];
elsif PSTATE.EL == EL2 then
```

```
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
    elsif CPTR_EL2.TTA == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        TRCSEQEVR[m] = X[t, 64];
elsif PSTATE.EL == EL3 then
    if CPTR_EL3.TTA == '1' then
        AArch64.SystemAccessTrap(EL3, 0x18);
    else
        TRCSEQEVR[m] = X[t, 64];
```

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94