

## TRCIDR9, ID Register 9

The TRCIDR9 characteristics are:

### Purpose

Returns the tracing capabilities of the trace unit.

### Configuration

AArch64 System register TRCIDR9 bits [31:0] are architecturally mapped to External register [TRCIDR9\[31:0\]](#).

This register is present only when FEAT\_ETE is implemented and FEAT\_TRC\_SR is implemented. Otherwise, direct accesses to TRCIDR9 are undefined.

### Attributes

TRCIDR9 is a 64-bit register.

### Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
RES0																															
NUMPOKEY																															
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0

#### Bits [63:32]

Reserved, res0.

#### NUMPOKEY, bits [31:0]

When **TRCIDR0.TRCDATA** != 0b00:

Indicates the number of P0 right-hand keys. Data tracing is not implemented in ETE and this field is reserved for other trace architectures. Allocated in other trace architectures.

#### Otherwise:

Reserved, res0.

## Accessing TRCIDR9

Accesses to this register use the following encodings in the System register encoding space:

### MRS <Xt>, TRCIDR9

op0	op1	CRn	CRm	op2
0b10	0b001	0b0000	0b0001	0b110

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
    && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
    when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
    elsif CPACR_EL1.TTA == '1' then
        AArch64.SystemAccessTrap(EL1, 0x18);
    elsif EL2Enabled() && CPTR_EL2.TTA == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
    IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
    SCR_EL3.FGTEn == '1') && HDFGRTR_EL2.TRCID == '1'
    then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            X[t, 64] = TRCIDR9;
    elsif PSTATE.EL == EL2 then
        if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
        && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
        when SDD == '1'" && CPTR_EL3.TTA == '1' then
            UNDEFINED;
        elsif CPTR_EL2.TTA == '1' then
            AArch64.SystemAccessTrap(EL2, 0x18);
        elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
            else
                X[t, 64] = TRCIDR9;
    elsif PSTATE.EL == EL3 then
        if CPTR_EL3.TTA == '1' then
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            X[t, 64] = TRCIDR9;
```

---

[AArch32  
Registers](#)

[AArch64  
Registers](#)

[AArch32  
Instructions](#)

[AArch64  
Instructions](#)

[Index by  
Encoding](#)

[External  
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.