		S	ł
P	S	e	u

SMLALB (indexed)

Signed multiply-add long to accumulator (bottom, indexed)

Multiply the even-numbered signed elements within each 128-bit segment of the first source vector by the specified signed element in the corresponding second source vector segment and destructively add to the overlapping double-width elements of the addend vector.

The elements within the second source vector are specified using an immediate index which selects the same element position within each 128-bit vector segment. The index range is from 0 to one less than the number of elements per 128-bit segment, encoded in 2 or 3 bits depending on the size of the element.

It has encodings from 2 classes: <u>32-bit</u> and <u>64-bit</u>

32-bit

```
3130292827262524 23 22 212019181716151413121110 9 8 7 6 5 4 3 2 1 0

0 1 0 0 0 1 0 0 1 0 0 1 i3h Zm 1 0 0 i3h Zm Zda

size<1>size<0> S U T
```

SMLALB <Zda>.S, <Zn>.H, <Zm>.H[<imm>]

```
if !HaveSVE2() && !HaveSME() then UNDEFINED;
constant integer esize = 16;
integer index = UInt(i3h:i3l);
integer n = UInt(Zn);
integer m = UInt(Zm);
integer da = UInt(Zda);
integer sel = 0;
```

64-bit

```
3130292827262524 23 22 21 20 19181716151413121110 9 8 7 6 5 4 3 2 1 0

0 1 0 0 0 1 0 0 1 1 1 1 | 1 | i2h | Zm | 1 0 0 0 | i2| 0 | Zn | Zda

size<1>size<0> S U T
```

SMLALB <Zda>.D, <Zn>.S, <Zm>.S[<imm>]

```
if !HaveSVE2() && !HaveSME() then UNDEFINED;
constant integer esize = 32;
integer index = UInt(i2h:i2l);
integer n = UInt(Zn);
integer m = UInt(Zm);
integer da = UInt(Zda);
integer sel = 0;
```

Assembler Symbols

<Zda> Is the name of the third source and destination scalable vector register, encoded in the "Zda" field.

<Zn> Is the name of the first source scalable vector register, encoded in the "Zn" field.

<Zm> For the 32-bit variant: is the name of the second source scalable vector register Z0-Z7, encoded in the "Zm" field.

For the 64-bit variant: is the name of the second source scalable vector register Z0-Z15, encoded in the "Zm" field.

<imm> For the 32-bit variant: is the element index, in the range 0
to 7, encoded in the "i3h:i3l" fields.

For the 64-bit variant: is the element index, in the range 0 to 3, encoded in the "i2h:i2l" fields.

Operation

```
CheckSVEEnabled();
constant integer VL = CurrentVL;
constant integer PL = VL DIV 8;
constant integer elements = VL DIV (2 * esize);
constant integer eltspersegment = 128 DIV (2 * esize);
bits(VL) operand1 = Z[n, VL];
bits(VL) operand2 = Z[m, VL];
bits(VL) result = Z[da, VL];

for e = 0 to elements-1
   integer s = e - (e MOD eltspersegment);
   integer element1 = SInt(Elem[operand1, 2 * e + sel, esize]);
   integer element2 = SInt(Elem[operand2, 2 * s + index, esize]);
   bits(2*esize) product = (element1 * element2) < 2*esize-1:0>;
   Elem[result, e, 2*esize] = Elem[result, e, 2*esize] + product;
Z[da, VL] = result;
```

Operational information

If FEAT_SVE2 is implemented or FEAT_SME is implemented, then if PSTATE.DIT is 1:

- The execution time of this instruction is independent of:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.
- The response of this instruction to asynchronous exceptions does not vary based on:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.

This instruction might be immediately preceded in program order by a MOVPRFX instruction. The MOVPRFX instruction must conform to all of the following requirements, otherwise the behavior of the MOVPRFX and this instruction is unpredictable:

- The MOVPRFX instruction must be unpredicated.
- The MOVPRFX instruction must specify the same destination register as this instruction.
- The destination register must not refer to architectural register state referenced by any other source operand register of this instruction.

BaseSIMD&FPSVESMEIndex byInstructionsInstructionsInstructionsInstructions

Internal version only: is a v33.64, AdvSIMD v29.12, pseudocode no_diffs_2023_09_RC2, sve v2023-06_rel ; Build timestamp: 2023-09-18T17:56

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.

Sh Pseu