ICH_ELRSR_EL2, Interrupt Controller Empty List Register Status Register

The ICH_ELRSR_EL2 characteristics are:

Purpose

These registers can be used to locate a usable List register when the hypervisor is delivering an interrupt to a VM.

Configuration

AArch64 System register ICH_ELRSR_EL2 bits [31:0] are architecturally mapped to AArch32 System register ICH_ELRSR[31:0].

This register is present only when FEAT_GICv3 is implemented and (EL2 is implemented or EL3 is implemented). Otherwise, direct accesses to ICH_ELRSR_EL2 are undefined.

If EL2 is not implemented, this register is res0 from EL3.

This register has no effect if EL2 is not enabled in the current Security state.

Attributes

ICH_ELRSR_EL2 is a 64-bit register.

Field descriptions



Bits [63:16]

Reserved, res0.

Status<n>, bit [n], for n = 15 to 0

Status bit for List register <n>, ICH_LR<n>_EL2:

Status<n>	Meaning

0b0	List register ICH_LR<n>_EL2, if implemented, contains a valid interrupt. Using this List register can result in overwriting a valid interrupt.
0b1	List register ICH_LR<n>_EL2 does not contain a valid interrupt. The List register is empty and can be used without overwriting a valid interrupt or losing an EOI maintenance interrupt.

For any List register <n>, the corresponding status bit is set to 1 if ICH_LR<n>_EL2.State is 0b00 and either ICH_LR<n>_EL2.HW is 1 or ICH_LR<n>_EL2.EOI (bit [41]) is 0.

Otherwise the status bit takes the value 0.

Accessing ICH_ELRSR_EL2

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, ICH_ELRSR_EL2

op0	op1	CRn	CRm	op2
0b11	0b100	0b1100	0b1011	0b101

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.NV == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    else
        UNDEFINED;
elsif PSTATE.EL == EL2 then
    if ICC_SRE_EL2.SRE == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    else
        X[t, 64] = ICH_ELRSR_EL2;
elsif PSTATE.EL == EL3 then
    if ICC_SRE_EL3.SRE == '0' then
        AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = ICH_ELRSR_EL2;
```

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94