AMCR_EL0, Activity Monitors Control Register

The AMCR_EL0 characteristics are:

Purpose

Global control register for the activity monitors implementation. AMCR_EL0 is applicable to both the architected and the auxiliary counter groups.

Configuration

AArch64 System register AMCR_EL0 bits [31:0] are architecturally mapped to AArch32 System register AMCR[31:0].

AArch64 System register AMCR_EL0 bits [31:0] are architecturally mapped to External register AMCR[31:0].

This register is present only when FEAT_AMUv1 is implemented. Otherwise, direct accesses to AMCR_EL0 are undefined.

Attributes

AMCR_EL0 is a 64-bit register.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
RES0																															
RES0															CG1RZ	RES0											HDBG	RES0			
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0

Bits [63:18]

Reserved, res0.

CG1RZ, bit [17]
When FEAT_AMUv1p1 is implemented:

Counter Group 1 Read Zero.

CG1RZ	Meaning

0b0	System register reads of AMEVCNTR1<n>_EL0 return the event count at all implemented and enabled Exception levels.
0b1	If the current Exception level is the highest implemented Exception level, system register reads of AMEVCNTR1<n>_EL0 return the event count. Otherwise, reads of AMEVCNTR1<n>_EL0 return a zero value.

Note

Reads from the memory-mapped view are unaffected by this field.

The reset behavior of this field is:

- On a Warm reset, this field resets to an architecturally unknown value.

Otherwise:

Reserved, res0.

Bits [16:11]

Reserved, res0.

HDBG, bit [10]

This bit controls whether activity monitor counting is halted when the PE is halted in Debug state.

HDBG	Meaning
0b0	Activity monitors do not halt counting when the PE is halted in Debug state.
0b1	Activity monitors halt counting when the PE is halted in Debug state.

The reset behavior of this field is:

- On a Warm reset, this field resets to an architecturally unknown value.

Bits [9:0]

Reserved, res0.

Accessing AMCR_EL0

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, AMCR_EL0

op0	op1	CRn	CRm	op2
0b11	0b011	0b1101	0b0010	0b000

```
if PSTATE.EL == EL0 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && CPTR_EL3.TAM == '1' then
        UNDEFINED;
    elsif AMUSERENR_EL0.EN == '0' then
        if EL2Enabled() && HCR_EL2.TGE == '1' then
            AArch64.SystemAccessTrap(EL2, 0x18);
        else
            AArch64.SystemAccessTrap(EL1, 0x18);
    elsif EL2Enabled() && CPTR_EL2.TAM == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && CPTR_EL3.TAM == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = AMCR_EL0;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && CPTR_EL3.TAM == '1' then
        UNDEFINED;
    elsif EL2Enabled() && CPTR_EL2.TAM == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && CPTR_EL3.TAM == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = AMCR_EL0;
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && CPTR_EL3.TAM == '1' then
        UNDEFINED;
    elsif HaveEL(EL3) && CPTR_EL3.TAM == '1' then
```

```
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
        else
            X[t, 64] = AMCR_EL0;
    elsif PSTATE.EL == EL3 then
        X[t, 64] = AMCR_EL0;
```

MSR AMCR_EL0, <Xt>

op0	op1	CRn	CRm	op2
0b11	0b011	0b1101	0b0010	0b000

```
if IsHighestEL(PSTATE.EL) then
    AMCR_EL0 = X[t, 64];
else
    UNDEFINED;
```

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94