

MAIR2_EL3, Extended Memory Attribute Indirection Register (EL3)

The MAIR2_EL3 characteristics are:

Purpose

Provides the memory attribute encodings corresponding to the possible AttrIdx values in a VMSAv8-64 or VMSAv9-128 translation table entry for stage 1 translations at EL1.

Configuration

This register is present only when FEAT_AIE is implemented. Otherwise, direct accesses to MAIR2_EL3 are undefined.

Attributes

MAIR2_EL3 is a 64-bit register.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
Attr7								Attr6								Attr5								Attr4							
Attr3								Attr2								Attr1								Attr0							
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0

Attr<n>, bits [8n+7:8n], for n = 7 to 0

Memory Attribute encoding.

When stage 1 Attributes Index Extension is enabled and AttrIdx[3] in a VMSAv8-64 or VMSAv9-128 translation table entry is 1, AttrIdx[2:0] gives the value of <n> in Attr<n>.

When stage 1 Attributes Index Extension is enabled and AttrIdx[3] in a VMSAv8-64 or VMSAv9-128 translation table entry is 0, see MAIR_ELx.Attr

Attr is encoded as follows:

Attr	Meaning
0b0000dd00	Device memory. See encoding of 'dd' for the type of Device memory.

Attr	Meaning
0b0000dd01	If FEAT_XS is implemented: Device memory with the XS attribute set to 0. See encoding of 'dd' for the type of Device memory. Otherwise, unpredictable.
0b0000dd1x	unpredictable.
0boooooiii, (oooo != 0000 and iii != 0000)	Normal memory. See encoding of 'oooo' and 'iii' for the type of Normal Memory.
0b01000000	If FEAT_XS is implemented: Normal Inner Non-cacheable, Outer Non-cacheable memory with the XS attribute set to 0. Otherwise, unpredictable.
0b10100000	If FEAT_XS is implemented: Normal Inner Write-through Cacheable, Outer Write-through Cacheable, Read-Allocate, No-Write Allocate, Non-transient memory with the XS attribute set to 0. Otherwise, unpredictable.
0b11110000	If FEAT_MTE2 is implemented: Tagged Normal Inner Write-Back, Outer Write-Back, Read-Allocate, Write-Allocate Non-transient memory. Otherwise, unpredictable.
0bxxxx0000, where xxxx != 0000 and xxxx != 0100 and xxxx != 1010 and xxxx != 1111	unpredictable.

'dd' is encoded as follows:

dd	Meaning
0b00	Device-nGnRnE memory
0b01	Device-nGnRE memory
0b10	Device-nGRE memory
0b11	Device-GRE memory

'oooo' is encoded as follows:

'oooo'	Meaning
0b0000	See encoding of Attr
0b00RW, RW not 0b00	Normal memory, Outer Write-Through Transient
0b0100	Normal memory, Outer Non-cacheable
0b01RW, RW not 0b00	Normal memory, Outer Write-Back Transient
0b10RW	Normal memory, Outer Write-Through Non- transient
0b11RW	Normal memory, Outer Write-Back Non- transient

R = Outer Read-Allocate policy, W = Outer Write-Allocate policy.

'iiii' is encoded as follows:

'iiii'	Meaning
0b0000	See encoding of Attr
0b00RW, RW not 0b00	Normal memory, Inner Write-Through Transient
0b0100	Normal memory, Inner Non-cacheable
0b01RW, RW not 0b00	Normal memory, Inner Write-Back Transient
0b10RW	Normal memory, Inner Write-Through Non- transient
0b11RW	Normal memory, Inner Write-Back Non- transient

R = Inner Read-Allocate policy, W = Inner Write-Allocate policy.

The R and W bits in 'oooo' and 'iiii' fields have the following meanings:

R or W	Meaning
0b0	No Allocate
0b1	Allocate

When FEAT_XS is implemented, stage 1 Inner Write-Back Cacheable, Outer Write-Back Cacheable memory types have the XS attribute set to 0.

The reset behavior of this field is:

- On a Warm reset, this field resets to an architecturally unknown value.

Accessing MAIR2_EL3

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, MAIR2_EL3

op0	op1	CRn	CRm	op2
0b11	0b110	0b1010	0b0001	0b001

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    UNDEFINED;
elsif PSTATE.EL == EL2 then
    UNDEFINED;
elsif PSTATE.EL == EL3 then
    X[t, 64] = MAIR2_EL3;
```

MSR MAIR2_EL3, <Xt>

op0	op1	CRn	CRm	op2
0b11	0b110	0b1010	0b0001	0b001

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    UNDEFINED;
elsif PSTATE.EL == EL2 then
    UNDEFINED;
elsif PSTATE.EL == EL3 then
```

```
MAIR2_EL3 = X[t, 64];
```

[AArch32
Registers](#)[AArch64
Registers](#)[AArch32
Instructions](#)[AArch64
Instructions](#)[Index by
Encoding](#)[External
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.