<u>Base</u>	SIMD&FP	<u>SVE</u>	<u>SME</u>	Index by
<u>Instructions</u>	<u>Instructions</u>	<u>Instructions</u>	<u>Instructions</u>	Encoding

Sh Pseu

SDIV

Signed Divide divides a signed integer register value by another signed integer register value, and writes the result to the destination register. The condition flags are not affected.

31 30 29 28 27 26 25 2	4 23 22 21 20 19 18 17 16	15 14 13 12 11 10 9 8 7 6 5	4 3 2 1 0
sf 0 0 1 1 0 1 0) 1 1 0 Rm	0 0 0 0 1 1 Rn	Rd
	-	01	

```
32-bit (sf == 0)

SDIV <Wd>, <Wn>, <Wm>
64-bit (sf == 1)

SDIV <Xd>, <Xn>, <Xm>

integer d = UInt(Rd);
integer n = UInt(Rn);
integer m = UInt(Rm);
constant integer datasize = 32 << UInt(sf);</pre>
```

Assembler Symbols

<wd></wd>	Is the 32-bit name of the general-purpose destination register, encoded in the "Rd" field.
<wn></wn>	Is the 32-bit name of the first general-purpose source register, encoded in the "Rn" field.
<wm></wm>	Is the 32-bit name of the second general-purpose source register, encoded in the "Rm" field.
<xd></xd>	Is the 64-bit name of the general-purpose destination register, encoded in the "Rd" field.
<xn></xn>	Is the 64-bit name of the first general-purpose source register, encoded in the "Rn" field.
<xm></xm>	Is the 64-bit name of the second general-purpose source register, encoded in the "Rm" field.

Operation

```
bits(datasize) operand1 = X[n, datasize];
bits(datasize) operand2 = X[m, datasize];
integer result;

if IsZero(operand2) then
   result = 0;
```

```
else
    result = RoundTowardsZero(Real(Int(operand1, FALSE)) / Real(Int(operand1, datasize)) / Real(Int(operand1, datasi
```

<u>Sh</u>

Pseu

BaseSIMD&FPSVESMEIndex byInstructionsInstructionsInstructionsInstructions

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode no diffs 2023 09 RC2, sve v2023-06 rel ; Build timestamp: 2023-09-18T17:56

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.