

IC IALLU, Instruction Cache Invalidate All to PoU

The IC IALLU characteristics are:

Purpose

Invalidate all instruction caches of the PE executing the instruction to the Point of Unification.

Configuration

AArch64 System instruction IC IALLU performs the same function as AArch32 System instruction [ICIALLU](#).

Attributes

IC IALLU is a 64-bit System instruction.

Field descriptions

This instruction has no applicable fields.

The value in the register specified by <Xt> is ignored.

Executing IC IALLU

The Rt field should be set to 0b11111. If the Rt field is not set to 0b11111, it is constrained unpredictable whether:

- The instruction is undefined.
- The instruction behaves as if the Rt field is set to 0b11111.

Accesses to this instruction use the following encodings in the System instruction encoding space:

IC IALLU{, <Xt>}

op0	op1	CRn	CRm	op2
0b01	0b000	0b0111	0b0101	0b000

```

if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.TPU == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() && HCR_EL2.TOCU == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
        IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
        SCR_EL3.FGTEn == '1') && HFGITR_EL2.ICIALLU == '1'
    then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() && HCR_EL2.FB == '1' then
        AArch64.IC(CacheOpScope_ALLUIS);
    else
        AArch64.IC(CacheOpScope_ALLU);
elsif PSTATE.EL == EL2 then
    AArch64.IC(CacheOpScope_ALLU);
elsif PSTATE.EL == EL3 then
    AArch64.IC(CacheOpScope_ALLU);

```

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.