

TRCSEQEVR<n>, Sequencer State Transition Control Register <n>, n = 0 - 2

The TRCSEQEVR<n> characteristics are:

Purpose

Moves the Sequencer state:

- Backwards, from state n+1 to state n when a programmed resource event occurs.
- Forwards, from state n to state n+1 when a programmed resource event occurs.

Configuration

External register TRCSEQEVR<n> bits [31:0] are architecturally mapped to AArch64 System register [TRCSEQEVR<n>\[31:0\]](#).

This register is present only when FEAT_ETE is implemented, FEAT_TRC_EXT is implemented and TRCIDR5.NUMSEQSTATE != 0b000. Otherwise, direct accesses to TRCSEQEVR<n> are res0.

Attributes

TRCSEQEVR<n> is a 32-bit register.

Field descriptions

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
RES0																B TYPE	RES0	B SEL	F TYPE	RES0	F SEL										

Bits [31:16]

Reserved, res0.

B_TYPE, bit [15]

Chooses the type of Resource Selector.

Backward field. Defines whether the backward resource event is a single Resource Selector or a Resource Selector pair. When the resource event occurs then the Sequencer state moves from state $n+1$ to state n . For example, if `TRCSEQEVR2.B.SEL == 0x14` then when event `0x14` occurs, the Sequencer moves from state 3 to state 2.

B_TYPE	Meaning
0b0	A single Resource Selector. <code>TRCSEQEVR<n>.B.SEL[4:0]</code> selects the single Resource Selector, from 0-31, used to activate the resource event.
0b1	A Boolean-combined pair of Resource Selectors. <code>TRCSEQEVR<n>.B.SEL[3:0]</code> selects the Resource Selector pair, from 0-15, that has a Boolean function that is applied to it whose output is used to activate the resource event. <code>TRCSEQEVR<n>.B.SEL[4]</code> is <code>res0</code> .

The reset behavior of this field is:

- On a Trace unit reset, this field resets to an architecturally unknown value.

Bits [14:13]

Reserved, `res0`.

B_SEL, bits [12:8]

Defines the selected Resource Selector or pair of Resource Selectors. `TRCSEQEVR<n>.B.TYPE` controls whether `TRCSEQEVR<n>.B.SEL` is the index of a single Resource Selector, or the index of a pair of Resource Selectors.

Backward field. Selects the single Resource Selector or Resource Selector pair.

If an unimplemented Resource Selector is selected using this field, the behavior of the resource event is unpredictable, and the resource event might fire or might not fire when the resources are not in the Paused state.

Selecting Resource Selector pair 0 using this field is unpredictable, and the resource event might fire or might not fire when the resources are not in the Paused state.

The reset behavior of this field is:

- On a Trace unit reset, this field resets to an architecturally unknown value.

F_TYPE, bit [7]

Chooses the type of Resource Selector.

Backward field. Defines whether the forward resource event is a single Resource Selector or a Resource Selector pair. When the resource event occurs then the Sequencer state moves from state n to state $n+1$. For example, if $\text{TRCSEQEVR1.F.SEL} == 0x12$ then when event $0x12$ occurs, the Sequencer moves from state 1 to state 2.

F_TYPE	Meaning
0b0	A single Resource Selector. $\text{TRCSEQEVR}\langle n \rangle.\text{F.SEL}[4:0]$ selects the single Resource Selector, from 0-31, used to activate the resource event.
0b1	A Boolean-combined pair of Resource Selectors. $\text{TRCSEQEVR}\langle n \rangle.\text{F.SEL}[3:0]$ selects the Resource Selector pair, from 0-15, that has a Boolean function that is applied to it whose output is used to activate the resource event. $\text{TRCSEQEVR}\langle n \rangle.\text{F.SEL}[4]$ is res0.

The reset behavior of this field is:

- On a Trace unit reset, this field resets to an architecturally unknown value.

Bits [6:5]

Reserved, res0.

F_SEL, bits [4:0]

Defines the selected Resource Selector or pair of Resource Selectors. $\text{TRCSEQEVR}\langle n \rangle.\text{F.TYPE}$ controls whether $\text{TRCSEQEVR}\langle n \rangle.\text{F.SEL}$ is the index of a single Resource Selector, or the index of a pair of Resource Selectors.

Forward field. Selects the single Resource Selector or Resource Selector pair.

If an unimplemented Resource Selector is selected using this field, the behavior of the resource event is unpredictable, and the resource event might fire or might not fire when the resources are not in the Paused state.

Selecting Resource Selector pair 0 using this field is unpredictable, and the resource event might fire or might not fire when the resources are not in the Paused state.

The reset behavior of this field is:

- On a Trace unit reset, this field resets to an architecturally unknown value.

Accessing TRCSEQEVR<n>

Must be programmed if [TRCRSCTLR<a>](#).GROUP == 0b0010 and [TRCRSCTLR<a>](#).SEQUENCER != 0b0000.

Writes are constrained unpredictable if the trace unit is not in the Idle state.

TRCSEQEVR<n> can be accessed through the external debug interface:

Component	Offset	Instance
ETE	$0 \times 100 + (4 * n)$	TRCSEQEVR<n>

This interface is accessible as follows:

- When OSLockStatus(), or !AllowExternalTraceAccess() or !IsTraceCorePowered(), accesses to this register generate an error response.
- Otherwise, accesses to this register are **RW**.

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.