

TRCIDR0, ID Register 0

The TRCIDR0 characteristics are:

Purpose

Returns the tracing capabilities of the trace unit.

Configuration

External register TRCIDR0 bits [31:0] are architecturally mapped to AArch64 System register [TRCIDR0\[31:0\]](#).

This register is present only when FEAT_ETE is implemented and FEAT_TRC_EXT is implemented. Otherwise, direct accesses to TRCIDR0 are res0.

Attributes

TRCIDR0 is a 32-bit register.

Field descriptions

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10
RES0	COMMTRANS	COMMOPT	TSSIZE	TSMARK	ITE	RES0	TRCEXDATA	QSUPP	QFILT	CONDTYPE	NUMEV										

Bit [31]

Reserved, res0.

COMMTRANS, bit [30]

Transaction Start element behavior.

COMMTRANS	Meaning
0b0	Transaction Start elements are P0 elements.
0b1	Transaction Start elements are not P0 elements.

COMMOPT, bit [29]

Indicates the contents and encodings of Cycle count packets.

COMMOPT	Meaning
0b0	Commit mode 0.
0b1	Commit mode 1.

The Commit mode defines the contents and encodings of Cycle Count packets, in particular how Commit elements are indicated by these packets. See the descriptions of these packets for more details.

Accessing this field has the following behavior:

- Access is **RAO/WI** if all of the following are true:
 - TRCIDR0.TRCCCI == 1
 - UInt(TRCIDR8.MAXSPEC) == 0x0
- When TRCIDR0.TRCCCI == 0, access to this field is **RAZ/WI**.
- Otherwise, access to this field is **RO**.

TSSIZE, bits [28:24]

Indicates that the trace unit implements Global timestamping and the size of the timestamp value.

TSSIZE	Meaning
0b00000	Global timestamping not implemented.
0b01000	Global timestamping implemented with a 64-bit timestamp value.

All other values are reserved.

This field reads as 0b01000.

TSMARK, bit [23]

When FEAT_ETEv1p1 is implemented:

Indicates whether Timestamp Marker elements are generated.

TSMARK	Meaning
0b0	Timestamp Marker elements are not generated.
0b1	Timestamp Marker elements are generated.

Otherwise:

Reserved, res0.

ITE, bit [22]**When FEAT_ETEv1p3 is implemented:**

Indicates whether Instrumentation Trace is implemented.

ITE	Meaning
0b0	Instrumentation Trace not implemented.
0b1	Instrumentation Trace implemented.

This field has the value 1 if FEAT_ITE is implemented.

This field has an implementation defined value.

Access to this field is **RO**.

Otherwise:

Reserved, res0.

Bits [21:18]

Reserved, res0.

TRCEXDATA, bit [17]**When TRCIDR0.TRCDATA != 0b00:**

Indicates if the trace unit implements tracing of data transfers for exceptions and exception returns. Data tracing is not implemented in ETE and this field is reserved for other trace architectures. Allocated in other trace architectures.

TRCEXDATA	Meaning
0b0	Tracing of data transfers for exceptions and exception returns not implemented.
0b1	Tracing of data transfers for exceptions and exception returns implemented.

Otherwise:

Reserved, res0.

QSUPP, bits [16:15]

Indicates that the trace unit implements Q element support.

QSUPP	Meaning
0b00	Q element support is not implemented.
0b01	Q element support is implemented, and only supports Q elements with instruction counts.
0b10	Q element support is implemented, and only supports Q elements without instruction counts.
0b11	Q element support is implemented, and supports: <ul style="list-style-type: none">• Q elements with instruction counts.• Q elements without instruction counts.

QFILT, bit [14]

Indicates if the trace unit implements Q element filtering.

QFILT	Meaning
0b0	Q element filtering is not implemented.
0b1	Q element filtering is implemented.

If TRCIDR0.QSUPP == 0b00 then this field is 0.

CONDTYPE, bits [13:12]

When TRCIDR0.TRCCOND == 1:

Indicates how conditional instructions are traced. Conditional instruction tracing is not implemented in ETE and this field is reserved for other trace architectures. Allocated in other trace architectures.

CONDTYPE	Meaning
0b00	Conditional instructions are traced with an indication of whether they pass or fail their condition code check.

0b01	Conditional instructions are traced with an indication of the APSR condition flags.
------	-----------------------------------------------------------------------------------------------------

All other values are reserved.

Otherwise:

Reserved, res0.

NUMEVENT, bits [11:10]

When TRCIDR4.NUMRSPAIR == 0b0000:

Indicates the number of ETEEvents implemented.

NUMEVENT	Meaning
0b00	The trace unit supports 0 ETEEvents.

All other values are reserved.

When TRCIDR4.NUMRSPAIR != 0b0000:

Indicates the number of ETEEvents implemented.

NUMEVENT	Meaning
0b00	The trace unit supports 1 ETEEvent.
0b01	The trace unit supports 2 ETEEvents.
0b10	The trace unit supports 3 ETEEvents.
0b11	The trace unit supports 4 ETEEvents.

Otherwise:

Reserved, res0.

RETSTACK, bit [9]

Indicates if the trace unit supports the return stack.

RETSTACK	Meaning
0b0	Return stack not implemented.

0b1	Return stack implemented.
-----	---------------------------

Bit [8]

Reserved, res0.

TRCCCI, bit [7]

Indicates if the trace unit implements cycle counting.

TRCCCI	Meaning
0b0	Cycle counting not implemented.
0b1	Cycle counting implemented.

This field reads as 1.

TRCCOND, bit [6]

Indicates if the trace unit implements conditional instruction tracing. Conditional instruction tracing is not implemented in ETE and this field is reserved for other trace architectures.

TRCCOND	Meaning
0b0	Conditional instruction tracing not implemented.
0b1	Conditional instruction tracing implemented.

This field reads as 0.

TRCBB, bit [5]

Indicates if the trace unit implements branch broadcasting.

TRCBB	Meaning
0b0	Branch broadcasting not implemented.
0b1	Branch broadcasting implemented.

This field reads as 1.

TRCDATA, bits [4:3]

Indicates if the trace unit implements data tracing. Data tracing is not implemented in ETE and this field is reserved for other trace architectures.

TRCDATA	Meaning
---------	---------

0b00	Data tracing not implemented.
0b11	Data tracing implemented.

All other values are reserved.

This field reads as 0b00.

INSTP0, bits [2:1]

Indicates if load and store instructions are P0 instructions. Load and store instructions as P0 instructions is not implemented in ETE and this field is reserved for other trace architectures.

INSTP0	Meaning
0b00	Load and store instructions are not P0 instructions.
0b11	Load and store instructions are P0 instructions.

All other values are reserved.

This field reads as 0b00.

Bit [0]

Reserved, res1.

Accessing TRCIDR0

TRCIDR0 can be accessed through the external debug interface:

Component	Offset	Instance
ETE	0x1E0	TRCIDR0

This interface is accessible as follows:

- When OSLockStatus() or !IsTraceCorePowered(), accesses to this register generate an error response.
- Otherwise, accesses to this register are **RO**.

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

