DC IGVAC, Invalidate of Allocation Tags by VA to PoC

The DC IGVAC characteristics are:

Purpose

Invalidate Allocation Tags in data cache by address to Point of Coherency.

Configuration

This instruction is present only when FEAT_MTE2 is implemented. Otherwise, direct accesses to DC IGVAC are undefined.

Attributes

DC IGVAC is a 64-bit System instruction.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
VA																															
VA																															
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0

VA, bits [63:0]

Virtual address to use. No alignment restrictions apply to this VA.

Executing DC IGVAC

When the instruction is executed, it can generate a watchpoint, which is prioritized in the same way as other watchpoints. If a watchpoint is generated, the CM bit in the ESR_ELx.ISS field is set to 1.

If EL0 access is enabled, when executed at EL0, the instruction may generate a Permission fault, subject to the constraints described in 'MMU faults generated by cache maintenance operations'.

Execution of this instruction might require an address translation from VA to PA, and that translation might fault. For more information, see 'The data cache maintenance instruction (DC)'.

Accesses to this instruction use the following encodings in the System instruction encoding space:

DC IGVAC, <Xt>

op0	op1	CRn	CRm	op2
0b01	0b000	0b0111	0b0110	0b011

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.TPCP == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
SCR_EL3.FGTEn == '1') && HFGITR_EL2.DCIVAC == '1'
then
        AArch64.SystemAccessTrap(EL2, 0x18);
    else
        AArch64.DC(X[t, 64], CacheType_Tag,
CacheOp_Invalidate, CacheOpScope_PoC);
elsif PSTATE.EL == EL2 then
    AArch64.DC(X[t, 64], CacheType_Tag,
CacheOp_Invalidate, CacheOpScope_PoC);
elsif PSTATE.EL == EL3 then
    AArch64.DC(X[t, 64], CacheType_Tag,
CacheOp_Invalidate, CacheOpScope_PoC);
```

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94