AArch32
Registers

AArch64
Registers

AArch32
Instructions

AArch64
Instructions

Index by
Encoding

External
Registers

# CTIDEVTYPE, CTI Device Type register

The CTIDEVTYPE characteristics are:

## Purpose

Indicates to a debugger that this component is part of a PE's cross-trigger interface.

## Configuration

CTIDEVTYPE is in the Debug power domain.

Implementation of this register is optional.

## Attributes

CTIDEVTYPE is a 32-bit register.

## Field descriptions

| 31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 | 7 6 5 4 | 3 2 1 0 |
|---|---|---|
| RES0 | SUB | MAJOR |

**Bits [31:8]**

Reserved, res0.

**SUB, bits [7:4]**

Subtype. Indicates this is a component within a PE.

Reads as `0b0001`.

Access to this field is **RO**.

**MAJOR, bits [3:0]**

Major type. Indicates this is a cross-trigger component.

Reads as `0b0100`.

Access to this field is **RO**.

# Accessing CTIDEVTYPE

**CTIDEVTYPE can be accessed through the external debug interface:**

| Component | Offset | Instance |
|-----------|--------|----------|
| CTI | 0xFCC | CTIDEVTYPE |

Accesses on this interface are **RO**.

28/03/2023 16:01; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94